



Modular Cooking Range Line 700XP 11 lt. Electric Multifunctional Cooker with compound bottom

ITEM # _____
MODEL # _____
NAME # _____
SIS # _____
AIA # _____



371109 (E7MFEDDD00)

11-Lt electric Multifunctional
Cooker with compound steel
cooking surface

Short Form Specification

Item No. _____

Heating via incoloy armoured heating elements. To be installed on 50 mm high feet for cleaning ease. Well to have rounded corners and cooking surface in compound steel (a 3mm layer of 316 AISI stainless steel on top of a 12mm layer of mild steel). Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- Multi purpose cooking appliance that can be used to shallow fry, cook liquids or even as a bain marie. Unit can be used for sautéing, poaching, steaming, simmering, stewing, braising, boiling and preparing white sauces.
- Well cooking surface made in compound steel (a 3mm layer of 316 AISI stainless steel on top of a 12mm layer of mild steel) for optimum grilling results.
- The stainless steel well to have rounded corners to facilitate cleaning.
- Bottom temperature control is precisely set by a thermostat on the control panel.
- Temperature can be set from 100 °C to 250 °C.
- Uniform temperature distribution over the whole base.
- Short heat-up time of the empty pan.
- Unit to be heated via incoloy armoured heating elements.
- Unit delivered with four 50 mm legs in stainless steel as standard (all round Stainless steel kick plates as option).

Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.
- Delivered with runners for gastronorm container.

APPROVAL: _____



Experience the Excellence
www.electroluxprofessional.com

Included Accessories

- 1 of Scraper for smooth plate fry tops PNC 164255
- 1 of Blades with rounded sides for scraper for multifunctional cookers PNC 921694

Optional Accessories

- Junction sealing kit PNC 206086 ☐
- Kit 4 wheels - 2 swivelling with brake - it is mandatory to install Base support and wheels PNC 206135 ☐
- Flanged feet kit PNC 206136 ☐
- Frontal kicking strip for concrete installation, 400mm PNC 206147 ☐
- Frontal kicking strip for concrete installation, 800mm PNC 206148 ☐
- Frontal kicking strip for concrete installation, 1000mm PNC 206150 ☐
- Frontal kicking strip for concrete installation, 1200mm PNC 206151 ☐
- Frontal kicking strip for concrete installation, 1600mm PNC 206152 ☐
- Frontal kicking strip, 400mm (not for refr-freezer base) PNC 206175 ☐
- Frontal kicking strip, 800mm (not for refr-freezer base) PNC 206176 ☐
- Frontal kicking strip, 1000mm (not for refr-freezer base) PNC 206177 ☐
- Frontal kicking strip, 1200mm (not for refr-freezer base) PNC 206178 ☐
- Frontal kicking strip, 1600mm (not for refr-freezer base) PNC 206179 ☐
- Kit 4 feet for concrete installation (not for 900 line free standing grill) PNC 206210 ☐
- 2 supports with side runners for 4 GN 1/1 containers for open base cupboards (multifunctional cookers, solid top and gas ranges with cupboard) PNC 206244 ☐
- Pair of side kicking strips PNC 206249 ☐
- Pair of side kicking strips for concrete installation PNC 206265 ☐
- Chimney upstand, 200mm PNC 206302 ☐
- Chimney upstand, 400mm PNC 206303 ☐
- Right and left side handrails PNC 206307 ☐
- Back handrail 800 mm PNC 206308 ☐
- Door for open base cupboard PNC 206350 ☐
- Base support for feet or wheels - 400mm (700/900) PNC 206366 ☐
- Base support for feet or wheels - 800mm (700/900) PNC 206367 ☐
- Base support for feet or wheels - 1200mm (700/900) PNC 206368 ☐
- Base support for feet or wheels - 1600mm (700/900) PNC 206369 ☐
- Base support for feet or wheels - 2000mm (700/900) PNC 206370 ☐

- Rear paneling - 600mm (700/900XP) PNC 206373 ☐
- Rear paneling - 800mm (700/900) PNC 206374 ☐
- Rear paneling - 1000mm (700/900) PNC 206375 ☐
- Rear paneling - 1200mm (700/900) PNC 206376 ☐
- Base support for feet or wheels - 600mm (700/900) PNC 206431 ☐
- 2 side covering panels for free standing appliances PNC 216000 ☐
- Frontal handrail, 400mm PNC 216046 ☐
- Frontal handrail, 800mm PNC 216047 ☐
- Frontal handrail, 1200mm PNC 216049 ☐
- Frontal handrail, 1600mm PNC 216050 ☐
- Large handrail - portioning shelf, 400mm PNC 216185 ☐
- Large handrail - portioning shelf, 800mm PNC 216186 ☐
- Lid for 11lt multifunctional cooker PNC 921689 ☐

Recommended Detergents

- C41 HI-TEMP RAPID DEGREASER, 1 pack of six 1 lt. bottles (trigger incl.) PNC 0S2292 ☐



Electric

5 kW

510 mm

Technical drawing of the front view of the 1000 Series 24 inch wide refrigerator. The drawing shows a top-down view of the refrigerator with various dimensions and callouts. The overall width is 24 inches (610 mm). The overall height is 52 11/16 inches (1340 mm). The top section features a control panel with two circular dials. The main body is a large rectangular compartment. The bottom section has two vertical drawers. Dimensions are provided in inches and millimeters. Callouts D, EI, and EQ point to specific features.

Dimensions:

- Overall Width: 24" (610 mm)
- Overall Height: 52 11/16" (1340 mm)
- Top Section Width: 2 3/16" (56 mm)
- Top Section Height: 11 5/16" (288 mm)
- Bottom Section Width: 2 3/16" (56 mm)
- Bottom Section Height: 0 7/16" (11 mm)

Callouts:

- D: Points to the top edge of the main compartment.
- EI: Points to the right edge of the main compartment.
- EQ: Points to the bottom edge of the main compartment.

Technical drawing of the front view of the cabinet, showing dimensions in inches and millimeters. The drawing includes a top panel with three screws, a handle on the right side, and two feet at the bottom. Dimensions are provided for overall height, width, and depth.

Dimension	Value (Inches)	Value (Millimeters)
Overall Height	34 1/16"	864 mm
Height to Top of Feet	27 9/16"	701 mm
Height of Feet	5 7/8"	149 mm
Overall Width	20 1/16"	510 mm
Width of Top Panel	20 11/16"	526 mm
Depth of Cabinet	3 9/16"	91 mm

EI = Electrical inlet (power)
 EQ = Equipotential screw

Technical drawing of the front view of the device. Dimensions are provided in inches and millimeters.

- Overall height: 21 15/16" (556 mm)
- Height of top bezel: 20 1/16" (510 mm)
- Height of bottom bezel: 28 3/4" (730 mm)
- Overall width: 15 3/4" (400 mm)
- Width of left bezel: 5 1/4" (134 mm)
- Feature 'D' is indicated by a dimension line pointing to the bottom bezel.
- Feature 'EI' is indicated by a dimension line pointing to the bottom bezel.



2025.11.26