specific	ations	S	!∶ <			
TME1000N-A Series				Project:		
ActiveCore Serie	es, 2 Door (Glass), L	Jpright Fridge			<u> </u>	
1130		Item No:				
Double glazed s	wing doors	475 745 1220				
50 695 Sign replacement panel, ————————————————————————————————————			5*			
or illuminated sign			Power cord			
LED interior ligh		SKOPE-connect [™] compatible controller	 4 × 10	00mm high sv		
	<u> </u>	Beloor clearance	(fro	ont lockable)	(Ø70 wheel)	
CABINET Model ID Doors	TME1000N-A 2 × self-closing, double glazed, sin	TME1000N-AC				
Doors	toughened safety glass swing door					
Internal door opening Shelves	2 × door openings: 1570mm high × 450mm wide 5 × adjustable height wire shelves: 1015mm wide × 470mm deep Sign replacement panel					
Sign Material	Sign replacement panel Powdercoat galvanized steel	DIMENSIONS				
PERFORMANCE				External	Internal	
Max. ambient temp.	40°C		Height Width	2200mm 1130mm	1570mm 1030mm	
Temperature range GEMS class	1°C to 4°C (adjustable via SKOPE- M1	connect 1°C to 15°C) M1	Depth	745mm	554mm	
GEMS energy consumption	3.79 kWh/24h	3.97 kWh/24h	Floor area	0.84m ²		
	\$415 p.a.(@ \$0.30/kWh)	\$435 p.a.(@ \$0.30/kWh)	Weight	225kg		
ELECTRICAL			* Depth 695mm exc	980L ludes removable do	or handle and door	
Electrical safety climate class			lock bracket			
0 0	2 × 1400mm, 15W LED 2 × 1400mm, 15W LED n.a. 1 × 1060mm, 12W LED		Dimensional tolera	inces		
Sign lighting	n.a.	Before installing this cabinet allow the following dimensional tolerances:				
Power cord Power supply	Supplied with 2.3m, 10 Amp plug a 220-240 Volts a.c. 50 Hz, single ph	Linear dimensions Overall cabinet dimensions				
Current draw	3.0 Amps (includes unit 2.6 Amps)	Less than 1 metre	±5mm			
REFRIGERATION			More than 1 metre	-5mm to +10mm Length of multip	ble cabinets	
	SCS Connect (SKOPE-connect™		At each joint	At each end wall		
Connectivity interface	Bluetooth	Less than 1 metre More than 1 metre	±5mm -5mm to +10mm	+15mm +15mm		
Refrigeration system		ActiveCore refrigeration unit (UTHCNI-		1		
	0010)		Ventilation require	Ventilation requirements		
Defining and t	,		Top	300mm		
Refrigerant	R290 / 99g (natural refrigerant)		Top Sides	300mm Not required		
Refrigerant Nominal capacity Heat rejection (Avg/peak)	,					

SKOPE Industries Limited reserve the right to alter specifications without notice. Copyright © 2018 SKOPE Industries Limited

Email: skope@skope.com, Website: www.skope.com





PSS0518 Rev. 2.8 Jul. 2020