HQ14SD




CATEGORY | GENERAL UPRIGHTS

RANGE QUARTZ

UNIT REFRIGERATOR

TYPE SELF CONTAINED


000RS | 1











CAPACITY LITRES 400 TEMPERATURE 1°C/4°C DIMENSIONS - W X D X H (ON CASTORS) MM 650 W x 730 D x 2040 H WEIGHT UNPACKED (KG) 150 STANDARD INCLUSIONS *** DOOR TYPE SD (Solid Door) FINISH (INTERIOR AND EXTERIOR, EXCLUDES REAR AND UNDER, STAINLESS STEEL INTERNAL FLOOR) SHELVES/DOOR 4 ELECTRICAL POWER SUPPLY 10 amp FRIDGE MODELS - SOLID RUNNING AMPS 3.0 GAS TYPE REFRIGERANT FRIDGE MODELS FOR OPTIONAL REMOTE UNITS				
TEMPERATURE 1°C/4°C DIMENSIONS - W X D X H (ON CASTORS) MM 650 W x 730 D x 2040 H WEIGHT UNPACKED (KG) 150 STANDARD INCLUSIONS *** DOOR TYPE SD (Solid Door) FINISH (INTERIOR AND EXTERIOR, EXCLUDES REAR AND UNDER, STAINLESS STEEL INTERNAL FLOOR) SHELVES/DOOR 4 ELECTRICAL POWER SUPPLY 10 amp FRIDGE MODELS - SOLID RUNNING AMPS DOORS GAS TYPE REFRIGERANT FRIDGE MODELS REFRIGERATION WATTAGES FOR OPTIONAL REMOTE UNITS	SPECIFICATIONS 1	S		
DIMENSIONS - W X D X H (ON CASTORS) MM WEIGHT UNPACKED (KG) STANDARD INCLUSIONS *** DOOR TYPE SD (Solid Door) FINISH (INTERIOR AND EXTERIOR, EXCLUDES REAR AND UNDER, STAINLESS STEEL INTERNAL FLOOR) SHELVES/DOOR GLECTRICAL POWER SUPPLY 10 amp FRIDGE MODELS - SOLID RUNNING AMPS DOORS GAS TYPE REFRIGERANT FRIDGE MODELS REFRIGERATION WATTAGES FOR OPTIONAL REMOTE UNITS	CAPACITY LITRES		400	
WEIGHT UNPACKED (KG) 150 STANDARD INCLUSIONS *** DOOR TYPE SD (Solid Door) FINISH (INTERIOR AND EXTERIOR, EXCLUDES REAR AND UNDER, STAINLESS STEEL INTERNAL FLOOR) SHELVES/DOOR 4 ELECTRICAL POWER SUPPLY 10 amp FRIDGE MODELS - SOLID RUNNING AMPS 3.0 GAS TYPE REFRIGERANT FRIDGE MODELS FOR OPTIONAL REMOTE UNITS	TEMPERATURE		1°C / 4 °C	
STANDARD INCLUSIONS *** DOOR TYPE SD (Solid Door) FINISH (INTERIOR AND EXTERIOR, EXCLUDES REAR AND UNDER, STAINLESS STEEL INTERNAL FLOOR) SHELVES/DOOR 4 ELECTRICAL POWER SUPPLY 10 amp FRIDGE MODELS - SOLID RUNNING AMPS DOORS GAS TYPE REFRIGERANT FRIDGE MODELS REFRIGERATION WATTAGES FOR OPTIONAL REMOTE UNITS	DIMENSIONS - W X D X H	I (ON CASTORS) MM	650 W x 730 D x 2040 H	
DOOR TYPE SD (Solid Door) FINISH (INTERIOR AND EXTERIOR, EXCLUDES REAR AND UNDER, STAINLESS STEEL INTERNAL FLOOR) SHELVES/DOOR 4 ELECTRICAL POWER SUPPLY 10 amp FRIDGE MODELS - SOLID RUNNING AMPS 3.0 GAS TYPE REFRIGERANT FRIDGE MODELS FOR OPTIONAL REMOTE UNITS	WEIGHT UNPACKED (KG)		150	
FINISH (INTERIOR AND EXTERIOR, EXCLUDES REAR AND UNDER, STAINLESS STEEL INTERNAL FLOOR) SHELVES/DOOR 4 ELECTRICAL POWER SUPPLY 10 amp FRIDGE MODELS - SOLID RUNNING AMPS 3.0 GAS TYPE REFRIGERANT FRIDGE MODELS REFRIGERATION WATTAGES FOR OPTIONAL REMOTE UNITS	STANDARD INCL	LUSIONS ***		
SHELVES/DOOR 4 ELECTRICAL POWER SUPPLY 10 amp FRIDGE MODELS - SOLID RUNNING AMPS DOORS GAS TYPE REFRIGERANT FRIDGE MODELS FOR OPTIONAL REMOTE UNITS	DOOR TYPE		SD (Solid Door)	
POWER SUPPLY 10 amp FRIDGE MODELS - SOLID RUNNING AMPS 3.0 GAS TYPE REFRIGERANT FRIDGE MODELS R134a REFRIGERATION WATTAGES FOR OPTIONAL REMOTE UNITS			CB (White), CBB (Black), SS (Stainless Steel)	
POWER SUPPLY 10 amp FRIDGE MODELS - SOLID BUNNING AMPS DOORS 3.0 GAS TYPE REFRIGERANT FRIDGE MODELS R134a REFRIGERATION WATTAGES FOR OPTIONAL REMOTE UNITS	SHELVES/DOOR		4	
FRIDGE MODELS - SOLID RUNNING AMPS 3.0 GAS TYPE REFRIGERANT FRIDGE MODELS R134a REFRIGERATION WATTAGES FOR OPTIONAL REMOTE UNITS	ELECTRICAL			
DOORS GAS TYPE REFRIGERANT FRIDGE MODELS R134a REFRIGERATION WATTAGES FOR OPTIONAL REMOTE UNITS	POWER SUPPLY		10 amp	
REFRIGERATION WATTAGES FOR OPTIONAL REMOTE UNITS REFRIGERATION WATTAGES FOR OPTIONAL REMOTE UNITS		RUNNING AMPS	3.0	
REFRIGERATION WATTAGES FOR OPTIONAL REMOTE UNITS	GAS TYPE			
	REFRIGERANT	FRIDGE MODELS	R134a	
	REFRIGERATION WATTAGES FOR OPTIONAL REMOTE UNITS			
FRIDGE MODELS - SOLID DOORS 400 @ -5°C SST	FRIDGE MODELS - SOLID DOORS		400 @ -5°C SST	

^{***} For **OPTIONS** refer to the current Williams Price Guide