



DICE1405 - Cube Ice Maker



| COBE | | | | | | |
|----------------------|--------------|--|--|--|--|--|
| FULL CUBE DIMENSIONS | | | | | | |
| W x D x H (mm) | 22 x 22 x 22 | | | | | |
| HALF CUBE DIMENSIONS | | | | | | |
| W x D x H (mm) | 10 x 22 x 22 | | | | | |

Ice Form

Features

- Space-saving 660mm tall design.
- Produces up to 623kg of ice per day.
- Harvest Assist provides consistent ice production for the life of the ice maker while reducing energy consumption and increasing capacity.
- Pure Ice® exclusively by Ice-O-Matic. Built-in antimicrobial protection for the life of the ice maker inhibits bacteria growth on ice maker surfaces. Coast's optional water filtration system provides protection against unpleasant tastes, odours and scale formation.
- Durable, electroless nickel plating on all evaporator plates ensures reliability.
- Constructed from corrosion-resistant stainless steel and fingerprint-proof plastic.
- Made in U.S.A

Warranty: 3 years parts and labour, and 5 years parts coverage on evaporator and compressor.

Options & Accessories

| Recommended Water Filter | | | | |
|--------------------------|-------------|--|--|--|
| System | Replacement | | | |
| CD20 | CD200 | | | |



SYDNEY OFFICE 46 Box Road Taren Point NSW 2229 Ph: (02) 9524 1234 Fax: (02) 9524 0968 Coast Distributors Pty Ltd ABN 86 002 020 162 www.coastdistributors.com.au November 2015 MELBOURNE OFFICE 25/44 Mahoneys Road Thomastown VIC 3074 Ph: (03) 9460 1095 Fax: (03) 94601357








Air Cooled

Please note: air-cooled units require (152 mm) clearance for air intake and exhaust.

- A. Ice maker potable water in, 3/8" FPT.
- B. Ice maker water out, 3/4" FPT.
- C. Hole for electrical connections, 7/8".
- D. Electrical junction box.

Dimensions

 $W \times D \times H (mm)$



C. D. C. D. C. D. C. T. D. C.

Operating Requirements

| | Minimum | Maximum (50Hz) |
|----------------------------|---------|----------------|
| Ambient Temp. Range Air | 10°C | 43°C |
| Water Temp. | 4.4°C | |
| Water Pressure | 1.4 BAR | 4.1 BAR |

Specifications

| | Model Cond. Unit | Cond. | Ice Production | | Water Usage | kWH Used | Watts Used | Voltage | Min. | Fuse | Approx. BTUs |
|--|---------------------|-------|---|--|---|---|--------------------------------------|-----------------|---------------------|------|-----------------|
| | | Unit | Per 24 hrs @ 21°C air / 10°C water | Per 24 hrs @ 32°C air / 21°C water | Litres per 45kg of ice @ 32°C air / 21°C water | Per 45 kg of ice @ 32°C air / 21°C water | Per Hr @ 32°C air / 21°C water | Characteristics | Circuit Ampacity | Size | Per hr |
| | ICE1405 | Air | 623kg | 486kg | 75 | 5.3 | 2360 | 220-240/50/1 | 21.7 | 30 | 21,185 |

Bin Chart Kits for Combining Wider Bins with Smaller Models

| Model | B25 | B40 | B42 | B55 | B100 | |
|---------|----------------|----------------|----------------|----------------|----------------|--|
| | 110kg capacity | 156kg capacity | 160kg capacity | 232kg capacity | 388kg capacity | |
| | 762mm width | 762mm width | 559mm width | 762mm width | 1219mm width | |
| ICE1405 | | N/A | | | | |

Notes

1,226 x 616 x 660

- Number of wires: 3 (including ground)
- Approx. Shipping Weight: 141kg
- R404A

SYDNEY OFFICE 46 Box Road Taren Point NSW 2229 Ph: (02) 9524 1234 Fax: (02) 9524 0968 Coast Distributors Pty Ltd ABN 86 002 020 162 www.coastdistributors.com.au November 2015 MELBOURNE OFFICE 25/44 Mahoneys Road Thomastown VIC 3074 Ph: (03) 9460 1095 Fax: (03) 94601357

agion