











| full Cube dimensions | | | | | | |
|----------------------|--------------|--|--|--|--|--|
| W x D x H (mm) | 22 x 22 x 22 | | | | | |
| HALF CUBE DIMENSIONS | | | | | | |
| W x D x H (mm) | 10 x 22 x 22 | | | | | |

Features

- Space-saving 510mm tall design.
- Produces up to 289kg of ice per day.
- Harvest Assist provides consistent ice production for the life of the ice maker while reducing energy consumption and increasing capacity.
- Pure Ice® exclusively by Ice-O-Matic. Built-in antimicrobial protection for the life of the ice maker inhibits bacteria growth on ice maker surfaces. Coast's optional water filtration system provides protection against unpleasant tastes, odours and scale formation.
- Durable, electroless nickel plating on all evaporator plates ensures reliability.
- Constructed from corrosion-resistant stainless steel and fingerprint-proof plastic.
- Made in U.S.A

Warranty: 3 years parts and labour, and 5 years parts coverage on evaporator and compressor.

Options & Accessories

| Recommended Water Filter | | | | |
|--------------------------|-----------------------|--|--|--|
| System | Replacement Cartridge | | | |
| CD10 | CD100 | | | |



COAST ICE & COLD SOLUTIONS





PICE0605 - Cube Ice Maker

Air Cooled

Please note: air-cooled units require 152 mm clearance for air intake and exhaust.

- A. Ice maker potable water in, 3/8" FPT.
- B. Ice maker water out, 3/4" FPT.
- C. Hole for electrical connections, 7/8".
- D. Electrical connection junction box.





Dimensions

| Model ICE605 | | | | | |
|----------------------------|-----------------|--|--|--|--|
| $W \times D \times H (mm)$ | 765 x 616 x 510 | | | | |

Operating Requirements

| | Minimum | Maximum (50Hz) |
|----------------------------|---------|----------------|
| Ambient Temp. Range Air | 10°C | 43°C |
| Water Temp. | 4.4°C | |
| Water Pressure | 1.4 BAR | 4.1 BAR |

Specifications

| Model | Cond. | Ice Pro | Ice Production Water Usage kWH Used Watts Used | | Watts Used | Voltage | Min. Circuit | Fuse | Approx. BTUs | |
|----------|-------|--|--|---|---|--------------------------------------|-----------------|----------|-----------------|--------|
| Model Ui | Unit | Per 24 hrs @ 21°C air / 10°C water | Per 24 hrs @ 32°C air / 21°C water | Litres per 45kg of ice @ 32°C air / 21°C water | Per 45 kg of ice @ 32°C air / 21°C water | Per Hr @ 32°C air / 21°C water | Characteristics | Ampacity | Size | Per hr |
| ICE0605 | Air | 289kg | 209kg | 83 | 5.8 | 1110 | 220-240/50/1 | 9.5 | 16 | 9,523 |

Bin Chart Kits for Combining Wider Bins with Smaller Models

| Model | B25 | B40 | B42 | B55 | B100 | CD40530 |
|---------|------------------|----------------|----------------|---------------------|-------------------------|---------------|
| | 110kg capacity | 156kg capacity | 160kg capacity | 232kg capacity | 388kg capacity | 81kg capacity |
| | 762mm width | 762mm width | 559mm width | 762mm width | 1219mm width | 762mm width |
| ICE0605 | Kit not required | | N/A | Kit not required | Bin Adapter Required | N/A |

Notes

- Number of wires: 3 (including ground)
- Approx. Shipping Weight: 89kg
- R404A

