	Electro	lux
--	---------	-----

Modular Cooking Range Line 900XP Full Module Electric Fry Top, Mild Steel

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		
AIA #		



Modular Cooking Range Line

900XP Full Module Electric Fry Top, Mild Steel

391069 (E9FTEHHS00)

Full module electric fry top with smooth horizontal mild steel plate, thermostatic control

391173 (E9FTEHHSON)

Electric fry top with smooth horizontal mild steel plate, thermostatic control

391070 (E9FTEHSP00)

Full module electric fry top with 2/3 smooth and 1/3 ribbed sloped mild steel plate, thermostatic control

(E9FTEHSPON)

Electric fry top with 2/3 smooth and 1/3 ribbed sloped mild steel plate, thermostatic control

Short Form Specification

Item No.

Unit to be Electrolux 900XP Full Module Electric Fry Top. Unit to have ___smooth or ___ 2/3 smooth and 1/3 ribbed cooking surface. Electric characteristics to be ___ 400 V or _ 230 V three phase. Cooking surface to be of mild steel. Unit to be installed on open base installations, bridging supports or cantilever systems. Unit to feature a collector on bottom the cooking surface for the collection of grease and fat. Body and work top of unit entirely in Stainless steel with Scotch Brite finish. Extra strength work top in heavy duty 2 mm Stainless steel. Unit has right-angled side edges to allow flush-fitting junction between units.

Main Features

- Unit to be mounted on open base cupboards, bridging supports or cantilever systems.
- Cooking surface in 15mm thick mild steel for optimum grilling results.
- Large drain hole on cooking surface permits the draining of fat into large 1 liter collector placed under the cooking surface.
- Electric elements in incoloy positioned under the cooking plate.
- Safety thermostat and thermostatic control.
- Units have separate controls for each half module of the cooking surface.
- Stainless steel high splash guards on the rear and sides of cooking surface. Splash guards can be easily removed for cleaning and are dishwasher-safe.
- The special design of the control knob system guarantees against water infiltration.
- IPX5 water protection.

Construction

- Cooking surface to be completely smooth or 2/3 smooth and 1/3 ribbed.
- Unit is 930 mm deep to give a larger working surface area.
- All exterior panels in Stainless Steel with Scotch Brite finishing.
- AISI 304 stainless steel worktop, 2mm thick.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

Included Accessories

• 1 of Stopper for fry top with horizontal plate (only for 391069, 206296 391173)

Optional Accessories

 Scraper for smooth plate fry tops PNC 164255 🗖 Junction sealing kit **PNC**

206086 🖵 Support for bridge type **PNC** installation, 800mm 206137 Support for bridge type **PNC**

installation, 1000mm Support for bridge type **PNC** installation, 1200mm

Support for bridge type installation, 1400mm

 Support for bridge type installation, 1600mm

206138 🗖

206139 **PNC** 206140 🗖

PNC 206141

APPROVAL:




Modular Cooking Range Line 900XP Full Module Electric Fry Top, Mild Steel

Water column with swivel arm (water column extension not included)	PNC	206289
• Water column extension for 900 line (not for 391174)	PNC	206290
 Stopper for fry top with horizontal plate (only for 391069, 391173) 	PNC	206296
• Chimney upstand, 800mm (only for 391069)	PNC	206304
 Grease/oil kit container for 700 line frytops (half and module) and 900 line frytops (module) 	PNC	206346
 Base support for feet or wheels - 800mm (700/900) 	PNC	206367
 Chimney grid net, 400mm (700XP/900) 	PNC	206400
 Scraper for ribbed plate fry tops - kit includes knife blades for both smooth and ribbed surface (only for 391070, 391174) 	PNC	206420
• Side handrail-right/left hand (900XP)	PNC	216044
• Frontal handrail, 800mm	PNC	216047
• Frontal handrail, 1200mm	PNC	216049
• Frontal handrail, 1600mm	PNC	216050
Water drain for full module fry tops	PNC	216153
 Large handrail - portioning shelf, 400mm 	PNC	216185
 Large handrail - portioning shelf, 800mm 	PNC	216186
 2 side covering panels for top appliances 	PNC	216278






Modular Cooking Range Line 900XP Full Module Electric Fry Top, Mild Steel



EI = Electrical connection EQ = Equipotential screw



Electric

Supply voltage:	
391069 (E9FTEHHS00)	400 V/3 ph/50/60 Hz
391173 (E9FTEHHSON)	230 V/3 ph/50/60 Hz
391070 (E9FTEHSP00)	400 V/3 ph/50/60 Hz
391174 (E9FTEHSP0N)	230 V/3 ph/50/60 Hz
Total Watts:	15 kW/

Key Information:

•	
Cooking surface width:	730 mm
Cooking surface depth:	700 mm
Working Temperature MIN:	120 °C
Working Temperature MAX:	280 °C
Net weight:	105 kg
Shipping weight:	
391069 (E9FTEHHS00)	105 kg
391173 (E9FTEHHSON)	120 kg
391070 (E9FTEHSP00)	105 kg
391174 (E9FTEHSP0N)	120 kg
Shipping height:	
391069 (E9FTEHHS00)	580 mm
391173 (E9FTEHHSON)	540 mm
391070 (E9FTEHSP00)	580 mm
391174 (E9FTEHSP0N)	540 mm
Shipping width:	1020 mm
Shipping depth:	860 mm
Shipping volume:	
391069 (E9FTEHHS00)	0.54 m³
391173 (E9FTEHHSON)	0.5 m³
391070 (E9FTEHSP00)	0.53 m ³
391174 (E9FTEHSPON)	0.5 m³
If appliance is set up or next to	: L

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.



Modular Cooking Range Line 900XP Full Module Electric Fry Top, Mild Steel