

SXX11698

Triple Action Quick Change System



Working pressure: 150-870kPa
Max. Temperature: 40 °C
Max. flow rate: 9 lpm
Nominal micron rating: 5

Caution: Do not use with water that is microbiologically unsafe or with water of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts.

SXX11698 twin filter system manufactured using NSF certified media for better reduction of chlorine, taste and odour and other offensive contaminants in the water. It will consistently provide food safe scale inhibition to prolong the life of water feed appliances.

It is designed for high water usage machine installations, the system offers a quick and easy bayonet cartridge to make changeovers a breeze. This high performance filter offers the latest filtration technology which provides huge sediment & chemical reduction capacity. It also dramatically reduces the development of scale to protect your equipment from costly breakdowns.

Reduces

- Sediment
- Chlorine
- Unpleasant taste and odour
- Organic contaminants
- Scale

The system comes with easy to install accessories.

- 2M 3/8" tube
- 2 x 3/4" female x 3/8" OD connector

Warning !

For commercial use with cold water only. Scheduled maintenance is recommended. Xsential cannot be liable for system failures due to improper maintenance.

www.xsential.com.au



Please the used filter to
Xsential
78 Daly St Ascot W.A. 6104
for recycle

SKOPE Industries Limited
57 Princess Street
Christchurch 8140
New Zealand
skope@skope.com