

Three Glass Swing Door BackBar

Range: BackBar
SKOPE ID: BB003
Dimensions: 2040mm (W) × 590mm (D) × 1025mm (H)*
Capacity: 635L

Project: _____

Item #: _____

* Height with castors is adjustable from 1015 to 1030.



A glass door under-bar fridge designed to merchandise ready-to-serve cold beverages in bars, restaurants, clubs, pubs, and cafés. Engineered to serve cold drinks at 0°C to 5°C (or adjustable up to 15°C) in ambient environments of up to 40°C. Made from powder-coated, galvanised steel with colour options, it can also be upgraded to full stainless-steel construction. The 'frameless' glass doors provide maximum product viewing and are designed for condensation protection in most environments via the double-glazed, argon-filled low-e insulated panels and heated fascia. For high humidity tropical environments heated-glass versions are available. The doors and cabinet are fitted with built-in retractable tabs to enable locking via padlock. The built-in LED lights provide optimum merchandising and can be dimmed or timed to turn on and off via a free smartphone app. The fridge uses R290 natural refrigerant for ultra-low energy consumption, low heat discharge and low noise output and can be provided in remote versions. The side-mounted fully removable refrigeration cartridge (with left and right options) is front-breathing and can be removed in line with best practice for safe servicing of flammable refrigerants. The fridge includes a controller that connects to a free app to enable the user to set temperatures and alerts, monitor temperatures and energy, and more. The fridge is certified to all Australian and New Zealand refrigeration and electrical safety standards.



Warranty




Natural Refrigerant



GEMS



SKOPE-connect



Cabinet

Type	BackBar
Finish	Powdercoat galvanised steel or stainless steel
Insulation	Type PU foam
	Thickness (mm) 50
	Blowing Agent Cyclo-iso Pentane (C5H10/C5H12)
Doors	Type Glass swing door (double-glazed, low-e, argon-filled)
	Opening Size Height (mm) 730 Width (mm) 460
Shelving	Six adjustable height, plastic-coated wire shelves 4 × outer shelf (497W × 440L), 2 × inner shelf (555W × 440L)
Lighting*	1 × 24W dimmable, cool white (5500-6500K) LED strip on cabinet ceiling

Dimensions†

	External	Internal	Packed
Width (mm)	2040	1580	TBC
Depth (mm)	590	530	TBC
Height (mm)	1025 (std. castors)	758	TBC
	920 (plinth mount)		
Weight (kg)	220	TBC	
Capacity (L)	635		
Footprint (m²)	1.2		

Ventilation (mm)

Top	Sides	Rear
Not required	Not required	Not required

Product Loading

	330ml can	600ml bottle
Facing	44	42
Loading	264	252

* Accessible via the free SKOPE-connect™ app.

† Allow for dimensional tolerances when installing the cabinet(s).

Performance

Product Temperature Range (°C)	1 to 4 (adjustable* from 0 to 15)
Rated Ambient Temperature	32°C/65% relative humidity
Maximum Ambient Temperature (°C)	40
Sound Level (dB(A))	Standard <66
	Hush Mode* <62

Greenhouse and Energy Minimum Standards (GEMS)

Star Rating	9
Product Temperature Class	M1 (-1 to 5°C)
Total Energy Consumption	2.81 kWh/24h
Annual Running Costs	\$307.70 (@ \$0.30/kWh)

Electrical

Supply	220-240 volts a.c., 50 Hz, single phase supply
Cord	1.9m power cord with 3-pin, 10 amp plug
Current draw (A)	2.2

Refrigeration

Controller	SCS Connect (SKOPE-connect™ compatible)
System Type	Removable cartridge
Cartridge Weight (kg)	24
Refrigerant/Charge	R290/81g
Nominal Capacity (W)	650
Heat Rejection (W)	Average 120 Peak 150
Remote Duty	n.a.
Defrost Type	Off-cycle
Drainage	No plumbing required



BB.3.GSW
on the SKOPE website