



Item # _____

We put space to work.

Job _____

Super Erecta Pro® Mobile Shelving

Durable and Cleanable. The original — reinnovated.

Corrosion resistant shelving constructed of removable polymer open grid shelf mats over a wire shelf frame. Shelf has a rigid four-sided frame with center truss(es). Robust corner provides complete 360° capture of the split sleeves and post for added stability. Shelf frames and posts have Metroseal epoxy coating over an electroplated substrate. Shelves with polymer mats offer a 15 year limited warranty against corrosion, while posts offer a 12 year warranty against corrosion. Microban® antimicrobial product protection is built into the frames, shelf mats, and posts. Industrial strength casters enable the shelving to easily move when you need it.

- **Preconfigured Units: include shelves, posts, casters, and bumpers under one easy-to-order model number. Choose models that fit the application: Rust resistant polymer casters for wet conditions. Chrome plated casters for general storage areas. Each cart uses 5" casters - two swivel and two swivel brake.**
- **Prolonged durability:** Polymer shelf mats are corrosion proof and impact resistant. They will not chip, rust, or corrode.
- **Easy to clean:** Removable polymer shelf mats can easily be lifted off the shelf frames for cleaning in sinks or wash/dish machines.
- **Strong and robust:** Steel corners, side and center supports assure a sturdy and stable weight bearing surface.
Weight capacities for evenly distributed loads:
800 lbs. (363kg) per shelf for lengths of 24" to 48" (610 to 1220mm)
600 lbs. (275kg) per shelf for lengths of 54" (1370mm) or longer
900 lbs. (408kg) per mobile unit.
- **Microban Product Protection:** Microban antimicrobial product protection is built into the shelf mats and the Metroseal 3 epoxy coating to protect the product from bacteria, mold, mildew, and fungus that cause odors and product degradation.
- **Efficient use of storage space:** Shelves can be adjusted at 1" (25mm) increments.
- **Open Grid Shelf Mats** promote air circulation and light penetration.
- **Fast, Easy Assembly:** Super Erecta Pro units assemble easily in minutes, without tools. SiteSelect posts have numbered grooves and feature unique double grooves every 8" (203mm) to help position the shelves.
- **Warranty against rust and corrosion:** Shelves with polymer shelf mats – 15 years. Posts – 12 years. Shelf mats are constructed of polypropylene and will never rust.



Super Erecta Pro with rust resistant casters



Super Erecta Pro with plated casters

Material Specifications

- **Shelf frames:** Carbon steel with Metroseal 3 epoxy coating.
- **Polymer Shelf mats:** polypropylene.
- **Microban antimicrobial product protection** is built into the polymer shelf mats and Metroseal 3 epoxy coating.
- **NSF listed for all environments.**
- **Continuous Temperature:** Super Erecta Pro Shelves can be used continuously within a range of -20/120° F (-29/49° C) with intermittent exposure to 200° F (93° C).
NOTE: Not suitable for cart wash applications.



All Metro Catalog Sheets are available on our website: www.metro.com



InterMetro Industries Corporation
North Washington Street, Wilkes-Barre, PA 18705
Product Information. U.S. and Canada: 1.800.992.1776
Outside U.S. and Canada: www.metro.com/contactus

LO2-247 10/20
Information and specifications are subject to change without notice. Please confirm at time of order.

Copyright © 2020 InterMetro Industries Corp.



Super Erecta Pro® Hybrid Polymer/Wire Mobile Shelving

10-83



We put space to work.®

Super Erecta Pro® Mobile Shelving

4-shelf unit - Nominal Height 68" (1727mm). Actual Height [68.438" (1738mm)]
 • Cart height will clear standard walk-in refrigeration doorway heights.

Actual dimensions including bumpers:
 Actual width, iadd 1/8" (3.2mm) to nominal width.
 Actual Length, add 1/8" (3.2mm) from nominal length.

| Nominal W x L | | Cat No with Rust Resistant Polymer Horn Casters | Approx. Pkd. Wt. | | Cat No. with Plated Casters | Approx. Pkd. Wt. | |
|---------------|----------|---|------------------|------|--------------------------------|------------------|------|
| in. | mm | | lbs. | kg | | lbs. | kg |
| 18x36 | 457x914 | PR-183668K3-MP-4 | 60.4 | 27.4 | PR-183668K3-MU-4 | 61.9 | 28.1 |
| 18x42 | 457x1060 | PR-184268K3-MP-4 | 67.2 | 30.5 | PR-184268K3-MU-4 | 68.7 | 31.2 |
| 18x48 | 457x1219 | PR-184868K3-MP-4 | 74.4 | 33.7 | PR-184868K3-MU-4 | 75.9 | 34.4 |
| 18x60 | 457x1524 | PR-186068K3-MP-4 | 88.4 | 40.1 | PR-186068K3-MU-4 | 89.9 | 40.8 |
| 21x36 | 530x914 | PR-213668K3-MP-4 | 67.2 | 30.5 | PR-213668K3-MU-4 | 68.7 | 31.2 |
| 21x42 | 530x1060 | PR-214268K3-MP-4 | 72.8 | 33.0 | PR-214268K3-MU-4 | 74.3 | 33.7 |
| 21x48 | 530x1219 | PR-214868K3-MP-4 | 79.6 | 36.1 | PR-214868K3-MU-4 | 81.1 | 36.8 |
| 21x60 | 530x1524 | PR-216068K3-MP-4 | 95.6 | 43.4 | PR-216068K3-MU-4 | 97.1 | 44.0 |
| 24x36 | 610x914 | PR-243668K3-MP-4 | 74.0 | 33.6 | PR-243668K3-MU-4 | 75.5 | 34.2 |
| 24x42 | 610x1060 | PR-244268K3-MP-4 | 78.1 | 35.4 | PR-244268K3-MU-4 | 79.6 | 36.1 |
| 24x48 | 610x1219 | PR-244868K3-MP-4 | 84.8 | 38.5 | PR-244868K3-MU-4 | 86.3 | 39.1 |
| 24x60 | 610x1524 | PR-246068K3-MP-4 | 102.8 | 46.6 | PR-246068K3-MU-4 | 104.3 | 47.3 |



4-shelf unit - Nominal Height 76" (1930mm). Actual Height [76.375" (1940mm)]
 • Cart height will clear most walk-in refrigeration doorway heights.

| Nominal W x L | | Cat No with Rust Resistant Polymer Horn Casters | Approx. Pkd. Wt. | | Cat No. with Plated Casters | Approx. Pkd. Wt. | |
|---------------|----------|---|------------------|------|--------------------------------|------------------|------|
| in. | mm | | lbs. | kg | | lbs. | kg |
| 18x36 | 457x914 | PR-183676K3-MP-4 | 62.4 | 28.3 | PR-183676K3-MU-4 | 63.9 | 29.0 |
| 18x42 | 457x1060 | PR-184276K3-MP-4 | 69.2 | 31.4 | PR-184276K3-MU-4 | 70.7 | 32.1 |
| 18x48 | 457x1219 | PR-184876K3-MP-4 | 76.4 | 34.7 | PR-184876K3-MU-4 | 77.9 | 35.3 |
| 18x60 | 457x1524 | PR-186076K3-MP-4 | 90.4 | 41.0 | PR-186076K3-MU-4 | 91.9 | 41.7 |
| 21x36 | 530x914 | PR-213676K3-MP-4 | 69.2 | 31.4 | PR-213676K3-MU-4 | 70.7 | 32.1 |
| 21x42 | 530x1060 | PR-214276K3-MP-4 | 74.8 | 33.9 | PR-214276K3-MU-4 | 76.3 | 34.6 |
| 21x48 | 530x1219 | PR-214876K3-MP-4 | 81.6 | 37.0 | PR-214876K3-MU-4 | 83.1 | 37.7 |
| 21x60 | 530x1524 | PR-216076K3-MP-4 | 97.6 | 44.3 | PR-216076K3-MU-4 | 99.1 | 45.0 |
| 24x36 | 610x914 | PR-243676K3-MP-4 | 76.0 | 34.5 | PR-243676K3-MU-4 | 77.5 | 35.2 |
| 24x42 | 610x1060 | PR-244276K3-MP-4 | 80.1 | 36.3 | PR-244276K3-MU-4 | 81.6 | 37.0 |
| 24x48 | 610x1219 | PR-244876K3-MP-4 | 86.8 | 39.4 | PR-244876K3-MU-4 | 88.3 | 40.1 |
| 24x60 | 610x1524 | PR-246076K3-MP-4 | 104.8 | 47.5 | PR-246076K3-MU-4 | 106.3 | 48.2 |



Rust resistant caster, 5PC



Plated caster, 5MP

4-shelf unit - Nominal Height 80" (1930mm). Actual Height [80.5 (2045mm)]

| Nominal W x L | | Cat No with Rust Resistant Polymer Horn Casters | Approx. Pkd. Wt. | | Cat No. with Plated Casters | Approx. Pkd. Wt. | |
|---------------|----------|---|------------------|------|--------------------------------|------------------|------|
| in. | mm | | lbs. | kg | | lbs. | kg |
| 18x36 | 457x914 | PR-183680K3-MP-4 | 62.4 | 28.3 | PR-183680K3-MU-4 | 63.9 | 29.0 |
| 18x42 | 457x1060 | PR-184280K3-MP-4 | 69.2 | 31.4 | PR-184280K3-MU-4 | 70.7 | 32.1 |
| 18x48 | 457x1219 | PR-184880K3-MP-4 | 76.4 | 34.7 | PR-184880K3-MU-4 | 77.9 | 35.3 |
| 18x60 | 457x1524 | PR-186080K3-MP-4 | 90.4 | 41.0 | PR-186080K3-MU-4 | 91.9 | 41.7 |
| 21x36 | 530x914 | PR-213680K3-MP-4 | 69.2 | 31.4 | PR-213680K3-MU-4 | 70.7 | 32.1 |
| 21x42 | 530x1060 | PR-214280K3-MP-4 | 74.8 | 33.9 | PR-214280K3-MU-4 | 76.3 | 34.6 |
| 21x48 | 530x1219 | PR-214880K3-MP-4 | 81.6 | 37.0 | PR-214880K3-MU-4 | 83.1 | 37.7 |
| 21x60 | 530x1524 | PR-216080K3-MP-4 | 97.6 | 44.3 | PR-216080K3-MU-4 | 99.1 | 45.0 |
| 24x36 | 610x914 | PR-243680K3-MP-4 | 76.0 | 34.5 | PR-243680K3-MU-4 | 77.5 | 35.2 |
| 24x42 | 610x1060 | PR-244280K3-MP-4 | 80.1 | 36.3 | PR-244280K3-MU-4 | 81.6 | 37.0 |
| 24x48 | 610x1219 | PR-244880K3-MP-4 | 86.8 | 39.4 | PR-244880K3-MU-4 | 88.3 | 40.1 |
| 24x60 | 610x1524 | PR-246080K3-MP-4 | 104.8 | 47.5 | PR-246080K3-MU-4 | 106.3 | 48.2 |

MICROBAN® and the MICROBAN® symbol are registered trademarks of the Microban® Products Company, Huntersville, NC. Microban® product protection does not by itself protect a user from food borne illness. Product must be routinely cleaned.

an Ali Group Company



The Spirit of Excellence