900XP 4-Burner Gas Range on Electric Oven

## Modular Cooking Range Line 900XP 4-Burner Gas Range on Electric Oven

ITEM #
MODEL #
NAME #
SIS #
AIA#
AIA #



391261 (E9GCGHTCEA)

4-Burner (1x10 kW, 3x6 kW) gas Range on electric Oven (6 kW) - AGA - Aus

# **Short Form Specification**

### Item No.

To be installed on stainless steel feet with height adjustment up to 50 mm. High efficiency flower flame burners with continuous power regulation and optimized combustion. Flame failure device as standard on burners to protect against accidental extinguishing. Oven chamber with 3 levels of runners to accomodate 2/1 GN shelves (2 steam pans). Ribbed, cast-iron oven base plate. Exterior panels of unit in stainless steel with Scotch Brite finish. Pan supports in heavy duty cast iron. Extra strength work top in heavy duty 2 mm stainless steel. Right-angled side edges to allow flush-fitting junction between units.

#### Main Features

- Flame failure device on each burner protects against gas leakage when accidental extinguishing of the flame occurs.
- IPX5 water protection.
- Large sized pan support in cast iron (stainless steel as option) with long center fins to allow the use of the largest down to the smallest pans.
- Oven chamber with 3 levels of runners to accomodate 2/1 GN shelves (2 steam pans).
- Protected pilot light.
- Ribbed cast iron oven base plate.
- The special design of the control knob system guarantees against water infiltration.
- Gas burners supplied for use with natural or LPG gas, conversion jets supplied as standard.
- Burners with optimized combustion.
- The three 6 kW and one 10 kW high efficiency burners are available in two different sizes to suit high performing cooking requirements of the most demanding customers:
  - -60 mm burners with continuous power regulation from 1,5 to 6 kW
  - -100 mm burners with continuous power regulation from 2.2 kW to 10 kW
- Unit to be mounted on stainless steel feet with height adjustment up to 50 mm. Unit can be easily mounted on cantilever systems.
- Base compartment consists of an electric standard oven with 40 mm thick oven door for heat insulation, positioned beneath the base plate.
- Oven thermostat adjustable from 110 °C to 285 °C or from 120 °C to 280 °C for model 391164.

## Construction

- Unit is 930 mm deep to give a larger working surface area.
- All exterior panels in Stainless Steel with Scotch Brite finishing.
- AISI 304 stainless steel worktop, 2mm thick.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

#### **Optional Accessories**

• GN2/1 chrome grid for static oven PNC 164250

Junction sealing kit
 PNC 206086 □
 Draught diverter, 150 mm diameter
 PNC 206132

#### APPROVAL:





# Modular Cooking Range Line 900XP 4-Burner Gas Range on Electric Oven

<ul> <li>Matching ring for flue condenser, 150 mm diameter</li> </ul>	PNC 206133 ☐
<ul> <li>Kit 4 wheels - 2 swivelling with brake - it is mandatory to install Base support and wheels</li> </ul>	PNC 206135
Flanged feet kit	PNC 206136 □
<ul> <li>Frontal kicking strip for concrete installation, 800mm</li> </ul>	PNC 206148 □
Frontal kicking strip for concrete installation, 1000mm	PNC 206150 □
Frontal kicking strip for concrete installation, 1200mm	PNC 206151 🗅
Frontal kicking strip for concrete installation, 1600mm	PNC 206152 □
Pair of side kicking strips for concrete installation	PNC 206157
Single burner radiant plate for pan support	PNC 206170
Single burner ribbed plate for direct cooking - fits frontal burners only	PNC 206172
Frontal kicking strip, 800mm (not for refr-freezer base)	PNC 206176
Frontal kicking strip, 1000mm (not for refr-freezer base)	PNC 206177
Frontal kicking strip, 1200mm (not for refr-freezer base)	PNC 206178
Frontal kicking strip, 1600mm (not for refr-freezer base)	PNC 206179
<ul> <li>Pair of side kicking strips (not for refr- freezer base)</li> </ul>	PNC 206180
2 panels for service duct for single installation	PNC 206181 🗖
• 2 panels for service duct for back to back installation	PNC 206202 □
• Kit 4 feet for concrete installation (not for 900 line free standing grill)	PNC 206210
<ul> <li>Flue condenser for 1 module, 150 mm diameter</li> </ul>	PNC 206246 □
<ul> <li>Water column with swivel arm (water column extension not included)</li> </ul>	PNC 206289 □
Water column extension for 900 line	PNC 206290 □
• Stainless steel double grid for 2 burners	PNC 206298 □
• Chimney upstand, 800mm	PNC 206304 □
Back handrail 800mm, Marine	PNC 206308 □
• Back handrail 1200mm, Marine	PNC 206309 □
• Wok pan support for open burners (700/900)	PNC 206363 □
• Base support for feet or wheels - 800mm (700/900)	PNC 206367 □
<ul> <li>Base support for feet or wheels - 1200mm (700/900)</li> </ul>	PNC 206368 □
<ul> <li>Base support for feet or wheels - 1600mm (700/900)</li> </ul>	PNC 206369 □
Base support for feet or wheels - 2000mm (700/900)	PNC 206370 □
• Rear paneling - 800mm (700/900)	PNC 206374 □
• Rear paneling - 1000mm (700/900)	PNC 206375 □


<ul> <li>Rear paneling - 1200mm (700/900)</li> </ul>	PNC 206376 🗆
<ul> <li>Chimney grid net, 400mm (700XP/900)</li> </ul>	PNC 206400 🗆
• Side handrail-right/left hand (900XP)	PNC 216044 🗖
• Frontal handrail, 800mm	PNC 216047 🗆
• Frontal handrail, 1200mm	PNC 216049 🗖
• Frontal handrail, 1600mm	PNC 216050 🗆
<ul> <li>2 side covering panels for free standing appliances</li> </ul>	PNC 216134 🗖
• Large handrail - portioning shelf, 800mm	PNC 216186 🗆
<ul> <li>Pressure regulator for gas units</li> </ul>	PNC 927225 🗅




Modular Cooking Range Line 900XP 4-Burner Gas Range on Electric Oven




## Modular Cooking Range Line 900XP 4-Burner Gas Range on Electric Oven





EI = Electrical inlet (power)
G = Gas connection



#### **Electric**

Predisposed for:

Gas

Gas Power: 28 kW

Standard gas delivery: Natural Gas G20 (20mbar)

Gas Type Option: LPG; Natural Gas

Gas Inlet: 1/2"

**Key Information:** 

Front Burners Power: 6 - 6 kW

Back Burners Power: 6 - 10 kW

**Back Burners Dimension -**

mm Ø 60 Ø 100

Front Burners Dimension -

mm Ø 60 Ø 60

Oven Heat Input: 6 kW

Oven working Temperature: 110 °C MIN; 285 °C MAX

**Oven Cavity Dimensions** 

(width): 575 mm

**Oven Cavity Dimensions** 

(height): 300 mm

**Oven Cavity Dimensions** 

(depth): 700 mm Net weight: 155 kg Shipping weight: 180 kg Shipping height: 1120 mm Shipping width: 900 mm Shipping depth: 1020 mm Shipping volume: 1.03 m<sup>3</sup> Certification group: N9CG

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat

insulation fitted.

