

Four Glass Sliding Door BackBar

Range: BackBar
SKOPE ID: BB014
Dimensions: 2600 mm (W) × 600 mm (D) × 1025 mm (H)*
Capacity: 860 L

Project: _____
Item #: _____

* Height with castors is adjustable from 1015 to 1030.



A glass door under-bar fridge designed to merchandise ready-to-serve cold beverages in bars, restaurants, clubs, pubs, and cafés. Engineered to serve cold drinks at 1°C to 4°C (or adjustable up to 15°C) in ambient environments of up to 32°C. Made from powder-coated, galvanised steel with colour options, it can also be upgraded to full stainless-steel construction. The glass doors are designed for condensation protection in most environments via the double-glazed, argon-filled low-e insulated panels and heated fascia. Sliding door locks are optional. The built-in LED lights provide optimum merchandising and can be dimmed or timed to turn on and off via a free smartphone app. The fridge uses R290 natural refrigerant for ultra-low-energy consumption, low heat discharge and low noise output and can be provided in remote versions. The side-mounted fully removable refrigeration cartridge (with left and right options) is front-breathing and can be removed in line with best practice for safe servicing of flammable refrigerants. The fridge includes a controller that connects to a free app to enable the user to set temperatures and alerts, monitor temperatures and energy, and more. The fridge is certified to all Australian and New Zealand refrigeration and electrical safety standards.



Warranty




Natural Refrigerant



GEMS



SKOPE-connect



Cabinet

Type	BackBar
Finish	Powdercoat galvanised steel or stainless steel
Insulation	Type PU foam
	Thickness (mm) 50
	Blowing Agent Cyclo-iso pentane (C5H10/C5H12)
Doors	Type Glass sliding door (double glazed, low-e, argon filled)
	Opening Size Height (mm) 730 Width (mm) 460
Shelving	Eight adjustable height plastic-coated wire shelves 4 × outer shelf (497W × 440D), 4 × inner shelf (555W × 440D)
Lighting*	2 × 16 W, cool white (5500-6500K) LED strips on cabinet ceiling

Dimensions†

	External	Internal	Packed
Width (mm)	2600	2140	TBC
Depth (mm)	600	530	TBC
Height (mm)	1025 (std. castors)	758	TBC
	920 (plinth mount)		
Weight (kg)	278	TBC	
Capacity (L)	860		
Footprint (m ²)	1.56		

Ventilation (mm)

Top	Sides	Rear
Not required	Not required	Not required

Product Loading

Facing	330 ml can	600 ml bottle
Loading	330	336

* Accessible via the free SKOPE-connect™ app.

† Allow for dimensional tolerances when installing the cabinet(s).

Performance

Product Temperature Range (°C)	1 to 4 (adjustable* from 0 to 15)
Maximum Ambient Temperature (°C)	32
Sound Level (dB(A))	Standard < 66
	Hush Mode* < 62

Greenhouse and Energy Minimum Standards (GEMS)

Star Rating	5
Product Temperature Class	M1 (-1 to 5°C)
Total Energy Consumption	8.17 kWh/24 h
Annual Running Costs	\$895 (@ \$0.30/kWh)

Electrical

Supply	220-240 volts a.c., 50 Hz, single phase supply
Cord	1.9 m power cord with 3-pin, 10 amp plug
Current draw (A)	4

Refrigeration

Controller	SCS Connect (SKOPE-connect™ compatible)
System Type	Removable cartridge
Cartridge Weight (kg)	24
Refrigerant/Charge	R290/81 g
Nominal Capacity (W)	850
Heat Rejection (W)	Average 340 Peak 365
Defrost Type	Automatic, off-cycle
Drainage	No plumbing required



BB.4.GSL
on the SKOPE website