GALA NG45 A R290



Self-Contained Ice Cube Maker

SKOPE ID: GALA NG45 A R290

Dimensions: 465mm (W) x 595mm (D) x 789mm (H) | 894 - 944mm (H w/ adjustable legs) Ice Production: 47kg per 24h (Air temperature 21°C, Water temperature 15°C) Storage Capacity: 20kg



Description

Self-contained ice maker producing gourmet-shaped, crystal-clear ice cubes, production 47kg/24 hours with reduced water usage and electricity. Virtually zero impact on the environment with R290 natural refrigerant. The ice maker is designed to complement high-end Scotch and Whiskey, as well as being perfect for cafés, as the gourmet ice cube is slow to melt reducing the impact on flavour. New electronic control enhances the performance and adapts to extreme climates, rated to 43 degrees Celsius. ITV patented Anti Scale Spray System works to avoid Limescale deposits and reduces vibrations. New Smart Front Ventilation System (SVFS) allows the self-contained units to be built in, new units also have an easy-to-access automatic cleaning switch at the front of the unit which disconnects the cooling cycle while circulating water and chemicals to clean the unit. The never-stop motor pump from ITV is designed without seals to prevent deterioration in hard water regions, and the units have a built-in lined storage bin which holds up to 20kg of ice. The unit can be ordered with an internal drain pump or without as standard. Self-contained units come with standard adjustable legs, and optional lockable castors 62mm high or 10mm levelling feet are available at an additional cost. Filter systems need to be installed with the ice machine to protect the 2-year parts and Labour warranty. Best suited to: Restaurants / Cafes, Clubs / Pubs / Bars, Hospitality / Venues, Accommodation.

Supplied Accessories





Drain Hose



Water Inlet Filter Gasket



Medium Scoop



Adjustable Height Legs



Backflow Prevention Device





Natural Refrigerant

Email: skope@skope.com



Watermark

A Watermark approved* water filter, suitable for the water type at the place of installation must be used. SKOPE can provide a water filter that protects the Ice Maker, and ensures proper function and high quality ice production. Service or repair due to absence of a suitable water filter will not be covered by SKOPE warranty. Contact SKOPE for more information.

*Watermark approval is only applicable to Australian installations. Elsewhere, a suitable water filter must be used

© 2021 SKOPE Industries Limited | We reserve the right to alter specifications without notice. AUS Freephone: 1800 121 535




NZ Freephone: 0800 947 5673

GALA NG45 A R290





LEFT SIDE VIEW



FRONTAL VIEW

REAR VIEW





Cabinet

Type Finish

Modular/Self Contained
Discussion in the second

Dimensions		
	External	Packed
Height (mm)	789	920
Width (mm)	465	540
Depth (mm)	595	660
Footprint (m ³)	0.33	
Weight		

Packed

56

Machine

45

AISI 304 Stainless Steel

Self Contained

GALA

weight
C
Gross (kg)

Performance & Operating Conditions

Max. Operating Temp.	43
Air Temperature	10°C - 43°C
Water Temperature	5°C - 38°C
Recommended Water Pressure	1 bar / 6 bar
Litres of Water p/h	5.3
100kg Kwh	26
Fuse	10
Heat Rejection (W)	1,025

Туре

System Type	Spray System
Refrigerant	R290 Natural Refrigerant
Heat Rejection (W)	1,025

Ice Specifications

Dimensions (mm)	39mm circumference x 35mm height
Ice cubes per cycle	24
Ice cube storage capacity (kg)	20

Ice Production per 24 hour cycle (kg) Water temperat

	water temperature				
		10°C	15°C	21°C	30°C
iture	10°C	47	50	44	41
Air temperature	21°C	47	47	47	45
Air te	32°C	45	44	43	40
	43°C	36	34	32	28



Optional Accessories

Water Filter	Water Filter Kit for Self-Contained (Part No. SXX11695)
Water Filter	Replacement Cartridge (Part No. SXX11696)
Drain Pump	Drain Pump PRO SA92 (Part No. SXX11725-P) This unit can also be ordered with a Drain Pump as standard
Castor Set	Set of 4 castors (Part No. ITV-31703)
Levelling Feet	Set of 4 10mm Levelling Feet (Part No. ITV-33007)
425	FASI STIE







GALA NG45 A R290 on the SKOPE website



AUS Freephone: 1800 121 535