## SPIKA NG150 A R290



## Self-Contained Ice Cube Maker

SKOPE ID: Half Dice - SPIKA NG150 A HD R290 & Full Dice - SPIKA NG150 A FD R290 Dimensions: 762mm (W) x 762mm (D) x 832mm (H) | 937 - 987mm (H w/ adjustable legs) Ice Production: 145kg per 24h (Air temperature 21°C, Water temperature 15°C) Storage Capacity: 45kg



### Description

Self-contained ice maker producing crystal-clear ice cubes in both half and full dice, production 145kg/24 hours with reduced water usage and electricity. Virtually zero impact on the environment with R290 natural refrigerant. The ice maker is designed to complement commercial bars, restaurants, pubs and night clubs with quick production of ice that cools the drink in seconds. New electronic control enhances the performance and adapts to extreme climates, rated to 43 degrees Celsius. New Smart Front Ventilation System (SVFS) allows the self-contained units to be built in, new units also have an easy-to-access automatic cleaning switch at the front of the unit which disconnects the cooling cycle while circulating water and chemicals to clean the unit. The never-stop motor pump from ITV is designed without seals to prevent deterioration in hard water regions, and the units have a built-in lined storage bin which holds up to 45kg of ice. Self-contained units come with standard adjustable legs, and optional lockable castors 62mm high or 10mm levelling feet are available at an additional cost. Filter systems need to be installed with the ice machine to protect the 2-year parts and Labour warranty. Best suited to: Restaurants / Cafes, Clubs / Pubs / Bars, Hospitality / Venues, Accommodation.

## **Supplied Accessories**





Adjustable Height Legs



**Backflow Prevention** Device





Natural Refrigerant





A Watermark approved\* water filter, suitable for the water type at the place of installation must be used. SKOPE can provide a water filter that protects the Ice Maker, and ensures proper function and high quality ice production. Service or repair due to absence of a suitable water filter will not be covered by SKOPE warranty. Contact SKOPE for more information.

\*Watermark approval is only applicable to Australian installations. Elsewhere, a suitable water filter must be used

© 2021 SKOPE Industries Limited | We reserve the right to alter specifications without notice.



Email: skope@skope.com AUS Freephone: 1800 121 535


NZ Freephone: 0800 947 5673

Last Revised 17 November 2022

# SPIKA NG150 A R290


SKOPE


#### SIDE VIEW



**FRONTAL VIEW** 

**REAR VIEW** 





#### Cabinet

Туре	SPIKA	
Finish	AISI 304 Stainless Steel	
Modular/Self Contained	Self Contained	
Dimensions		
	External	Packed
Height (mm)	832 (937-987 w adjustable legs)	950
Width (mm)	762	840
Depth (mm)	762	825
Footprint (m <sup>3</sup> )	0.66	
Weight		
	Machine	Packed
Gross (kg)	74	85

#### Performance & Operating Conditions

Max. Operating Temp.	43	
Air Temperature	10°C - 43°C	
Water Temperature	5°C - 38°C	
<b>Recommended Water Pressure</b>	1 bar / 6 bar	
	Full Dice	Half Dice
Litres of Water p/h	10.2	10.7
100kg Kwh	12.5	14.1
Plug Set Size	10 Amps	10 Amps
Heat Rejection (W)	1,363	1,363

#### Туре

Vertical Evaporator System Refrigerant R290 Natural Refrigerant


**Ice Specifications** 

	Full Dice	Half Dice
Dimensions (mm)	26 x 23 x 26mm	23 x 11 x 26mm
Ice cubes per cycle	144	288
Ice cube storage capacity (kg)	45	45

#### Ice Production per 24 hour cycle (kg)

#### Water temperature

		10°C	15°C	21°C	30°C
iture	10°C	155	150	136	121
Air temperature	21°C	148	145	130	115
Air te	32°C	125	120	107	92
	43°C	105	100	90	75



#### **Optional Accessories**

Water Filter	Water Filter Kit for Modular (Part No. SXX11698)
Water Filter	Replacement Cartridge (Part No. SXX11696)
Drain Pump	Drain Pump PRO SA92 (Part No. SXX11725-P)
Castor Set	Set of 4 castors (Part No. ITV-31703)
Levelling Feet	Set of 4 10mm Levelling Feet (Part No. ITV-33007)





SPIKA NG150 A R290 on the SKOPE website

Email: skope@skope.com

AUS Freephone: 1800 121 535 Last Revised 17 November 2022

NZ Freephone: 0800 947 5673