



Merrychef High Speed Cook Oven

conneX 12 HP





conneX12 HP


conneX12 B HP

Standard Features

- All in one unit to rapidly cook, toast, grill and reheat fresh or frozen food - eliminating need for other appliances
- Cooking up to 20 times faster than other cooking methods
- Large oven cavity to suit up to 305 x 305mm / 12" plate size
- Fits on a 600mm bench depth
- · Ventless cooking capabilities through built in catalytic converter
- High speed Technology® combines three heat technologies: microwave, convection heat and tuned impingement
- Energy efficient with quick pre-heat, cool down times and low energy usage in standby mode
- Easy to operate with 7" HD widescreen display with robust glass
- EasyTouch 2.0 icon driven controller with unlimited storage for multi-stage cooking profiles
- Each cooking profile offers up to 6 stages with programmable cooking times, microwave power settings and written / pictorial user instructions for each stage
- Self-diagnostics capability to monitor components
- Easy menu updates or data transfer via USB
- Wi-fi / ethernet connection
- Quiet operation < 48 dbA
- Cool to touch exterior allows for zero space at the sides and back
- · Patented easy access front mounted air filter
- Stainless steel cavity and casework
- Easy clean cavity with sealed rounded edges

Includes

- Flat cook plate
- Guarded paddle with sides
- Full size cooking tray
- Cool down pan
- Cook plate liners (2)
- · Cleaning care package, consisting of:
 - 1x oven cleaner (bottle)
 - 1x oven protector (bottle)




How it works

The convection fan pulls air in through the back of the cavity (1). This is then heated and returned to the cavity through the catalytic converters (2) and impinger plate (3) to produce an even heat pattern in the oven. This heat pattern allows food to cook evenly and produces a crisp golden finish, every time.



Merrychef High Speed Cook Oven

conneX 12 HP



MICROWAVE POWER

Microwave settings, off or 5-100% in 1% increments Distribution system, rotating active antennae

CONVECTED HEAT

Temperature settings OFF and from 100° to 275°C in 1°C steps

Distribution system, Tuned Impingement

VENTILATION

Ventless certification, EPA 202 tested (8hr) Internal catalytic filtration to limit grease and odour emission

DIMENSIONS

Width	357 mm
Depth	643 mm
Height	619 mm
Weight	58.7 kg

PACKED DIMENSIONS

Width	520 mm
Depth	820 mm
Height	855 mm
Weight (including cleaning system)	68.7 kg

INSTALLATION REQUIREMENTS

Rear				0 mm
Right				0 mm
Left				0 mm
Top				50 mm
777		1.0	 1.	

The item is not intended for built-in application For precise installation instructions please refer to the units installation manual

ELECTRICAL SUPPLY

ELECTRICAL SOLI EL	
2 phase model	
400-415, 50Hz (2P+N+E)	
Rated power consumption:	5.8kW
Rated current:	20A
20A 5 pin plug	
Mains cable length	1.8m
All Merrychef ovens require a D type circuit	
breaker for all installations	

POWER OUTPUT (APPROX.)

Microwave	2.0 kW
Convected heat	2.2 kW
Combination mode	2.0** + 2.2 kW
www.	

**This is approximate microwave power output.

MOFERT

Australia moffat.com.au

New Zealand moffat.co.nz

Australia Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Ph 03-9518 3888 Fax 03-9518 3833 vsales@moffat.com.au www.moffat.com.au

New South Wales Ph 02-8833 4111 nswsales@moffat.com.au

South Australia Ph 03-9518 3888 vsales@moffat.com.au

Queensland Ph 07-3630 8600 qldsales@moffat.com.au

Western Australia Ph 08-9413 2400 wasales@moffat.com.au

New Zealand Moffat Limited

Christchurch 45 Illinois Drive Izone Business Hub Rolleston 7675 New Zealand Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz

Auckland Ph +64 9-574 3150 sales@moffat.co.nz

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd AN MC 22 08



