

EC Series Self Contained Gourmet Ice Machines – with Progressive Water Discharge – up to 93kg

ECS 206 AS OX Small gourmet cube 8g, Ø21mm x 25mm



Small gourmet cube
8g, 21mm dia x H 25mm



Note: Ice production rate is measured with the water temperature at 10°C and an ambient temperature of 21°C.


- Up to 93kg daily production rate
- 50kg storage bin capacity
- Air cooled version
- Produces individual transparent Gourmet crystal clear supercubes
- PWD-Progressive water discharge: pumps excess residual water up to a distance up to 15 meters
- XSafe - Natural Sanitation System
- Agion Technology resists the growth of microbes and the development of unpleasant odours
- Simple, reliable electromechanic controls
- Horizontal ice evaporator spray-system technology
- Resistant stainless steel exterior
- Front access condenser air filter, removable and washable
- Easy access front ON-OFF switch
- Routine maintenance visible alarm light on front panel
- Ergonomically designed ice storage access with disappearing door and door closing movement dampening system
- Includes ice scoop, water and drain hose



XSafe

EC Series Self Contained Gourmet Ice Machines – with Progressive Water Discharge – up to 93kg

ECS 206 AS OX



moffat.com.au

Australia
Moffat Pty Limited
Victoria/Tasmania
740 Springvale Road
Mulgrave, Victoria 3170
Telephone 03-9518 3888
Facsimile 03-9518 3833
vsales@moffat.com.au

New South Wales
Telephone 02-8833 4111
nswsales@moffat.com.au

South Australia
Telephone 03-9518 3888
vsales@moffat.com.au

Queensland
Telephone 07-3630 8600
qldsales@moffat.com.au

Western Australia
Telephone 08-9413 2400
wasales@moffat.com.au

Ice production per 24 hours

Ambient temperature / Water temperature

10°C / 10°C	21°C / 10°C	32°C / 21°C
100	93	72

Dimensions

Width:	1250mm
Depth:	622mm
Height:	809mm (including legs)
Nett weight:	84kg
Packed weight:	97kg

Water consumption

Air cooled version: 7.5 litres per hour

Electrical rating

Air cooled version: 230-240V, 1P+N+E, 50Hz, 950W,
10A cordset supplied

No. Circuit wire:	3
Compressor:	2100W
Energy consumption:	21.3kW/24hr

Refrigerant type

R404a

Installation distance from wall

Rear	150mm
Sides	150mm
Operating requirement air temperature 10-43°C	

Water connection requirements

Inlet connection:	R ¾"
Cold water:	5-38°C
Pressure:	100-500kPa
Water outlet connection:	Ø¾"

Important Notice:
Models and specifications are subject to change without notice. This spec sheet is meant for commercial purpose only. For technical documentation please refer to our service manuals.



© Copyright Moffat Ltd
AU.SM.2201