



EC Series Self Contained Gourmet Ice Machines – with Progressive Water Discharge – up to 152kg ECS 226 AS OX Small gourmet cube 8g, Ø21mm x 25mm



Small gourmet cube 8g, 21mm dia x H 25mm



Note: Ice production rate is measured with the water temperature at 10°C and an ambient temperature of 21°C.

- Up to 152kg daily production rate
- 70kg storage bin capacity
- Air cooled version
- Produces individual transparent Gourmet crystal clear supercubes
- PWD-Progressive water discharge: pumps excess residual water up to a distance up to 15 meters
- XSafe Natural Sanitation System .
- Agion Technology resists the growth of microbes and • the development of unpleasant odours
- Simple, reliable electromechanic controls
- Horizontal ice evaporator spray-system technology
- Resistant stainless steel exterior
- Front access condenser air filter, removable and washable
- Easy access front ON-OFF switch

- Routine maintenance visible alarm light on front panel
- Ergonomically designed ice storage access with disappearing door and door closing movement dampening system
- Includes ice scoop, water and drain hose


















EC Series Self Contained Gourmet Ice Machines – with Progressive Water Discharge – up to 152kg **ECS 226 AS OX**








- 1. 3/4" OD OVERFLOW DRAIN 2. 3/4" GAS - WATER INLET
- 3/4" GAS WATER OUTLET WATER COOLED UNIT ONLY
- 4. 3/4" GAS WATER INLET
- WATER COOLED UNIT ONLY
- 5. CORD SET







moffat.com.au

Australia Moffat Pty Limited Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone 03-9518 3888 Facsimile 03-9518 3833

vsales@moffat.com.au New South Wales Telephone 02-8833 4111 nswsales@moffat.com.au

South Australia

Telephone 03-9518 3888 vsales@moffat.com.au

Queensland Telephone 07-3630 8600 qldsales@moffat.com.au

Western Australia Telephone 08-9413 2400 wasales@moffat.com.au

Ice production per 24 hours

슌

10°C / 10°C 21°C / 10°C 32°C / 21°C	Ambient temperature / Water temperature			
	10°C / 10°C	21°C / 10°C	32°C / 21°C	

155	152	100

Dimensions Width

Υ

Bunononono	
Width:	1078mm
Depth:	719mm
Height:	1082mm (including legs)
Nett weight:	98kg
Packed weight:	112kg

Water consumption

Air cooled version: 17 litres per hour

Electrical rating

Air cooled version: 230-240V, 1P+N+E, 50Hz, 1500W, 10A cordset supplied

No. Circuit wire: 3 Compressor: 2571W Energy consumption: 24.7kW/24hr

Refrigerant type

R404a

Installation distance from wall

Rear 150mm 150mm Sides Operating requirement air temperature 10-43°C

Water connection requirements

Inlet connection: R 3/4" 5-38°C Cold water: Pressure: 100-500kPa Water outlet connection: ؾ"

Important Notice:

Models and specifications are subject to change without notice. This spec sheet is meant for commercial purpose only. For technical documentation please refer to our service manuals.



© Copyright Moffat Ltd AU.SM.2201

an Ali Group Company

