30DSERIES



E31D4 / VH31

Technical data sheet for

E31D4 OVEN / VH31 VENTLESS HOOD ON THE SK2731N STAND

GN 1/1 Digital / Electric Convection Oven with **Halton** Ventless Condensing Hood on a Stainless Steel Stand



STANDARD FEATURES

- 4 Gastronorm GN 1/1 pan capacity
- 80mm tray spacing
- Compact 616mm depth x 810mm width
- Digital display Time and Temperature Controls
- USB port for programs
- Programmable for up to 30 programs
- Grill mode
- Single direction low-velocity fan
- 2.8kW heating in bake mode / 2kW grill elements
- Safe-Touch vented side hinged door
- Stay-Cool door handle
- Vitreous enameled oven chamber

STANDARD FEATURES – VENTLESS CONDENSION HOOD

- Removes need for installation under canopy or ducted oven hood
- Complies with EPA202 test method for less than <5mg/m³ grease laden effluent limits
- 3 stage filtering including charcoal odour filter
- Condensing heat exchanger for oven vent condensing and reduced heat emissions
- Self contained condensate collection no connection to waste drain required
- Oven Hood interlock control
- Automatic 2 speed extraction fans reduced noise/energy
- SEED certified for installation without an extraction canopy in most situations

VHIK31 INSTALLATION KIT

- Supplied standard with Hood
- Requires mechanical and electrical field assembly for connection of Hood to Oven

ACCESSORIES

- Turbofan SK2731N Oven Stand
- #H11715 Replacement Charcoal Filter for VH31



E31D4

Unit shall be a Moffat electrically heated Turbofan Convection Oven. The oven shall have a one piece vitreous enamel oven chamber, stainless top and sides and safe touch vented easy clean side hinged door that offers field reversible hinging. Oven shall have capacity for four GN 1/1 pans and include a top grilling oven element and grill operating mode. The oven shall be controlled by an electronic control having separate digital displays and adjusting knobs for time and temperature functions. The oven control shall allow both manual and programmed operating modes and have separate control keys for selection of Grill mode, oven light function and timer operation. The unit shall include a halogen oven lamp. Oven shall be able to be bench mounted on 76mm feet or mounted on oven stand model SK2731N. Oven shall be fitted with a 15A cordset. Unit shall be supplied in 100% recyclable shipping packaging.

SK2731N

Unit shall be a Moffat Turbofan stainless steel oven stand. The stand shall be constructed from stainless steel tube with castors, with front castors having dual swivel and wheel locks. It shall be fitted with 6 tray runners suitable for 600 x 400 trays and GN 1/1 pans. The stand shall be fully compatible with and support Turbofan Convection Oven models E27M2, E27M3, E28M4, and E31D4. Unit shall be supplied in 100% recyclable shipping packaging.

VH31

Unit shall be a Halton Ventless Condensing Hood, UL listed and UL EPH classified. The unit shall have all stainless steel construction, include 3 stage filtration and incorporate a condensing heat exchanger. Unit will feature an automatic 2 speed extraction fan with interlocked oven operation, Unit shall be 220-240V and fitted with a 10A plug cordset. Unit shall be provided with VHIK31 Installation Kit for connection and fitment to Moffat Turbofan Convection Oven model E31D4.

VHIK31 Installation Kit

Installation Kit shall be provided with VH31 Ventless Condensing Hood. Installation kit shall include: Wire harness for oven interlock connection to oven controls. Four 100mm oven feet and condensate collection pan and housing for self-contained condensate collection. Oven rear shroud for protection of interlock control harness and condensate drain tube. Oven to stand rear securing plate when oven is fitted on a Moffat Turbofan SK2731N Stand.

Halton VH Series Ventless Condensing Hoods are manufactured by Halton Company, USA, exclusively for Moffat Turbofan Convection Ovens.



30DSERIES

turbofan

E31D4 / VH31

E31D4 GN 1/1 Digital / Electric Convection Oven

CONTROLS

Electronic controls with Digital Time and Temperature display,

Manual or Program modes Grill mode quick select key Thermostat range 50-260°C

Timer range from 180 minutes in countdown mode

Timer range up to 999 minutes in time count mode for holding.

slow cooking

Over-temperature safety cut-out

SPECIFICATIONS

Electrical Requirements

230-240V, 50Hz, 1P+N+E, 3.1kW, 12.9A

15A cordset fitted

External Dimensions (E31D4)

810mm

Height 625mm including 76mm feet

Depth 616mm

Oven Internal Dimensions Width 565mm 425mm Height 395mm Depth Volume 0.09m3

Oven Rack Dimensions 540mm Depth 370mm Nett Weight (E31D4)

53.8kg

Packing Data (E31D4)

68.2kg 0.45m³

Width 740mm Height 720mm Depth

VH31 Ventless Condensing Hood Including VHIK31 Installation Kit

CONTROLS

Illuminated Power switch Oven interlocked control

SPECIFICATIONS

Electrical Requirements 220-240V, 50-60hz, 1P+N+E, 1.0A

10A plug 1.8M cordset fitted

Water Requirements

No water connection required

Drain Requirements - Optional

Hood water condensate can be taken to a water waste drain if desired. 1800mm long 3/8"OD drain hose is supplied with hood. External Dimensions (VH31 Ventless Hood)

Width 818mm Height 364mm Depth 852mm Allow 76mm rear clearance

Nett Weight (VH31 Ventless Hood) 46.0 kg

Packing Data (VH31 Ventless Hood) 68 kg

0.46 m³

875mm Width: 545mm Height Depth: 965mm

SK2731N Stainless Steel Stand

All stainless steel welded frame oven stand for Turbofan

E27, E28 and E31 Series model ovens

6 position tray runners standard 76mm diameter wheel swivel castors standard with 2 front

castors with dual swivel and wheel Supplied CKD for assembly on site

External Dimensions (SK2731N Oven Stand)

810mm Width Height 880mm 650mm Depth

Nett Weight (SK2731N Oven Stand)

19.5kg

Packing Data (SK2731N Oven Stand)

22kg 0.11 m³

> 830mm Width 805mm Height

Depth 160mm

INSTALLATION CLEARANCES

Rear 25mm LH Side 25mm RH Side 25mm

CLEARANCE FROM SOURCES OF HEAT

A minimum distance of 300mm from the appliance sides

is required

MOFFAT

Australia www.moffat.com.au New Zealand www.moffat.co.nz www.turbofanoven.com

Australia Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone +61 3-9518 3888 Facsimile +61 3-9518 3833 vsales@moffat.com.au

New South Wales Telephone +61 2-8833 4111 nswsales@moffat.com.au

South Australia Telephone +61 3-9518 3888 vsales@moffat.com.au

Queensland Telephone +61 7-3630 8600 qldsales@moffat.com.au

Western Australia Telephone +61 8-9413 2400 wasales@moffat.com.au

New Zealand Moffat Limited

Christchurch 45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz

Auckland Telephone +64 9-574 3150 sales@moffat.co.nz





Quality Management SGS Standard

Designed and manufactured by





ISO9001

All Turbofan products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection. ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice

Copyright Moffat Ltd AN.TFN.S.2201

















an Ali Group Company

HALTON VH31 VENTLESS HOOD

