

FAST FRI SINGLE PAN GAS FRYER 600mm

FN8130G



- High performance single pan fish fryer
- Patented infra-red burner system
- Easy clean stainless steel open pan with 10 year limited warranty
- 31L oil capacity
- 2 large or 3 standard basket capacity
- Large capacity cool zone
- 32mm (1 1/4") drain valve
- Stainless steel exterior
- Easy service
- Fully modular
- Low back model (FNL) available

Overall Construction

- Stainless steel pan with 10 year limited warranty
- Bull nose welded 1.5mm 304 stainless steel
- Splashback 1.5mm 304 stainless steel
- Side panels 1.2mm 304 stainless steel
- Double skin door with 0.9mm 304 stainless exterior
- 32mm (1 1/4") drain valve
- 150mm legs in 63mm dia. heavy-duty 1.2mm 304 stainless steel with adjustable feet
- 3 standard baskets and stainless steel lid supplied standard

Controls

- Direct action thermostat reacts to + or -1.0° C
- Thermostat range 145 195°C
- Over-temperature safety cut-out
- Millivolt gas valve system (no electrical supply)
- Flame failure protection on each pilot
- Piezo ignition to standing pilot burners

Cleaning and Servicing

- Open stainless steel pans for easy clean
- Easy clean basket support bar
- 32mm (1 1/4") drain valve for effective draining
- Easy clean stainless steel exterior
- \bullet Access to all parts from front of unit

Technical data sheet for



FAST FRI SINGLE PAN GAS FRYER 600mm

Specifications Production rate

Production rate
31kg/hr
Pan Size
Width 515mm
Length 380mm
Oil frying depth 95mm
Oil capacity 31L (46.5lbs shortening)
Rackets

3 chrome plated wire baskets
140mm W x 335mm D x 145mm H
Optional 2 chrome plated large wire baskets
210mm W x 335mm D x 145mm H Stainless steel perforated basket support plate

2 x 45MJ/hr infra-red burners Gas Power

90MJ/hr, 25kW Gas connection

3³/₄ (BSP) male 300mm from RH side, 35mm from rear, and 125mm from floor

Optional rear connection (refer specification drawing)
All units incorporate Natural and LP gas regulator

DIMENSIONS

Width 600mm Depth 805mm Height 915mm Incl. splashback 1130mm Incl. low back 1085mm

NETT WEIGHT 95kg


PACKING DATA 0.70m3, 143kg Width 870mm


Depth 645mm Height 1255mm

GAS TYPES Available in Natural gas and LP gas Please specify when ordering Units supplied complete with gas type conversion kits Other gas types on request


OPTIONS AT EXTRA COSTWaldorf Filtamax filtration system Fish plates Extra standard baskets Large baskets Side splash guards Joining caps Castors Plinth mounting

FN8130G





805 92



MOFFAT

moffat.com.au moffat.co.nz

Australia moffat.com.au

Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone +613-9518 3888 Facsimile +613-9518 3833 vsales@moffat.com.au

New South Wales Telephone +612-8833 4111 nswsales@moffat.com.au

South Australia Telephone +613-9518 3888 vsales@moffat.com.au

Queensland Telephone +617-3630 8600 qldsales@moffat.com.au

Western Australia Telephone +618-9413 2400 wasales@moffat.com.au

New Zealand moffat.co.nz

Moffat Limited

Rolleston 45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz

Auckland Telephone +64 9-574 3150 sales@moffat.co.nz





ISO9001 Quality Management SGS Standard



Cert. No. 6882

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd AN.W8.08/19

The Spirit of Excellence