

## AL8 Passthrough Warewasher W 905mm x D 760mm x H 1745mm



Washtech warewashers are built to improve the efficiency of operations washing oversized and/or heavily soiled items, from bakeries to production kitchens, supermarkets to hospitals. This is achieved with a continuous and consistent wash process throughout the day that is easy on your staff. With highly efficient water consumption rates, they are also light on the environment and operating costs.

The AL8 is a powerful, highly durable, simple-to-use and easy-to-maintain passthrough warewasher. It features Washtech hybrid controls which combine IP67 stainless switches, tried-and-tested switchgear, with a customisable electronic timer. Built with a large wash chamber and counterbalanced passthrough door, the AL8 is ideal for washing bins, crates, bowls and other oversized items.

Since 1981 Washtech dishwashers have been constructed from heavy-duty stainless steel, and are engineered specifically for Australian conditions and regulations. Backed by the most extensive service network and spare parts inventory in the region, your Washtech AL8 will not let you down.

#### **Standard Features**

- Versatile 2, 4 and 6 minute wash cycles
- Large internal wash chamber with useable area of W 700mm x D 540mm x H 650mm
- Low hot water consumption of 2.6 litres per cycle
- Washtech hybrid controls
- Easy installation supplied with:
- Water supply hose
  - Detergent and rinse aid pumps with injector lines
- High powered wash system
- Suitable for connection to low inlet water temperature and/or pressure (break tank and rinse pump fitted)
- Heavy-duty stainless steel construction and wash manifold
- Robust stainless steel wash and rinse arms with precision stainless steel jets
- Double heavy-duty stainless steel filtration system including dual scrap trays and separate wash inlet filter
- Wash chamber easily accessible via counter-sprung hood
- Easy loading with inline bench work
- Watermark approved backflow prevention
- Moffat's comprehensive 5-2-1 Warranty

#### Includes:

- 1 x 500x600mm dish rack (600 70042)
- 1 x 500x600mm cup rack (600 70043)
- 1 x 435mm cup cover (K0452)
- 1 x cutlery basket (C660508)
- 1 x cutlery container (C660503)







## **WASHTECH**

# AL8

### MOFFRT

moffat.com.au washtech.com.au

#### **Moffat Pty Limited**

#### VIC/TAS/SA

70 Springvale Road Mulgrave, Victoria 3170 Telephone 03-9518 3888 Fax 03-9518 3833 vsales@moffat.com.au

#### NSW

Telephone 02-8833 4111 nswsales@moffat.com.au

#### QLD


Telephone 07-3630 8600 qldsales@moffat.com.au


#### WA

Telephone 08-9413 2400 wasales@moffat.com.au

In line with policy to continually develop and improve its products, Washtech reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd Version: WAL80020 2103





A – Hot Water*					
Temperature	65°C				
Connection	3/4" male; hose supplied				
Pressure	100-350kPa				
Flow	10 litres per min				
Quality	Potable - refer table				
Backflow Prevention AVB					
Consumption	2.6 litres per cycle				
B - Waste					
Connection	1.5" BSP male				
Line	2.0" / 50mm minimum				

C – Electrical	v	Hz	A/phase	Max kW
Three Phase	415	50	25	18.00
Three Phase	415	50	15	10.50

Dimensions Machine Packed Width (mm) 905 1000 Depth (mm) 760 910 Height (mm) 1745 1650 Weight (kg) 155 180 Volume (m<sup>3</sup>) 1.50 Water Quality Min Max 8 pН 7 Hardness (ppm) 20 100 Cl-100  $SO_4$ 400 Fe 0.1 Mn 0.5 Cu 0.05  $Cl_2$ 0.1

25

Isolating switch must be within 1m of, and not directly behind the machine.

\* Suitable for connection to cold inlet water. For optimal productivity, use hot inlet water.

Refer to operator manual for installation instructions.







