Technical data sheet for

GAS COOKTOPS 300mm

RN8200G-B, RN8203G-B





RN8200G-B

- Heavy-duty construction
- 28 MJ/hr open burners
- Flame failure standard
- Pilot burners optional
- 300mm griddle plate option
- Optional simmer plates
- Stainless steel exterior
- Easy clean
- Easy service
- Fully modular
- Low back models (RNL) available

Overall Construction

Сооктор

- Welded hob with 1.5mm 304 stainless steel bull nose
- Splashback and side panels 1.2mm 304 stainless steel
- Front panels 0.9mm 304 stainless steel
- Aluminised steel internal construction
- Cast iron 28MJ/hr open burners with forged brass cap
- Vitreous enamelled cast iron potstands
- Vitreous enamelled open burner spill cover
- Cast iron simmer plates (optional extra)
- 12mm thick mild steel griddle plate
- 2.5mm 304 stainless steel griddle splash guards
- Vitreous enamelled spill trays

BENCH MOUNT (SUPPLIED AS -B MODEL)

- Four 63mm dia. heavy-duty 1.2mm 304 stainless steel bench legs with adjustable feet.
- Adjustable height 80mm 105mm

Controls

- Variable high to low controls to open burners
- Open burners flame failure standard with pilot burners optional
- Variable high to low controls to griddles
- Griddles standard with pilot, flame failure and piezo ignition
- Large easy use control knob heat resistant reinforced
- Easy view control settings on knob

Cleaning and Servicing

- All models with easy clean stainless steel external finish
- Lift off burners heads and vitreous enamelled burner spill covers
- Vitreous enamelled spill trays under open burner and griddle section
- Access to all parts from front of unit

Technical data sheet for

GAS COOKTOPS 300mm



SpecificationsBurners
Open Burners 28MJ/hr dual flame ring with

simmer rate Griddle Burners 20MJ/hr

Gas power RN8200G 56 MJ/hr, 15.5kW RN8203G 20 MJ/hr, 5.5kW Griddle Plate

300mm Griddle cooking surface 292mm x 475mm, 1387cm2

292mm x 475mm, 1387cm2

Gas connection

R ¹/₂ (BSP) male

100mm from RH side, 32mm from rear,
and 70mm from floor

All units supplied with Natural and LP gas regulator

DIMENSIONS

Width 300mm Depth 805mm Height 315mm Incl. splashback 530mm Incl. low back 370mm

NETT WEIGHT 47kg

PACKING DATA

0.20m3, 70kg Width 870mm Depth 350mm Height 665mm

GAS TYPES


Available in Natural gas and LP gas Please specify when ordering Units supplied complete with gas type conversion kits

Other gas types on request

OPTIONS AT EXTRA COST

Simmer plates (replaces Potstand) Ribbed griddle plates Joining caps

RN8200G-B, RN8203G-B



RN8200G-B



RN8203G-B



MOFFAT

moffat.com.au moffat.co.nz

Australia moffat.com.au

Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone +613-9518 3888 Facsimile +613-9518 3833 vsales@moffat.com.au

New South Wales Telephone +612-8833 4111 nswsales@moffat.com.au

South Australia Telephone +613-9518 3888 vsales@moffat.com.au

Queensland Telephone +617-3630 8600 qldsales@moffat.com.au

Western Australia Telephone +618-9413 2400 wasales@moffat.com.au

New Zealand moffat.co.nz

Moffat Limited

Rolleston 45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz

Auckland Telephone +64 9-574 3150 sales@moffat.co.nz





ISO9001 Quality Management SGS Standard



Cert. No. 6902

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd AN.W8.08/19