# Waldorf Bold

# Electric Cooktops 900mm

RNLB8600E-B, RNLB8600E-CD, RNLB8600E-LS, RNLB8600E-RB, RNLB8603E-B, RNLB8603E-CD, RNLB8603E-LS, RNLB8603E-RB, RNLB8606E-B, RNLB8606E-CD, RNLB8606E-LS, RNLB8606E-RB, RNLB8609E-B, RNLB8609E-CD, RNLB8609E-LS, RNLB8609E-RB,



RNLB8600E-CD

- Heavy-duty construction
- 2.0kW hot plate elements
- Optional 2.4kW open radiant elements
- 300mm, 600mm, and 900mm griddle plate options
- 3 models of base unit
- 1 model of refrigerated base with two GN 1/1 drawers
- Stainless steel exterior
- Black vitreous enamel finish to front panels 0
- Easy clean ٠
- Easy service
- Fully modular

# Series Options

RNLB - Low back models RNB - 215mm splashback option

## OVERALL CONSTRUCTION

- COOKTOP
- · Welded hob with 1.5mm 304 stainless steel bull nose
- · Splashback and side panels 1.2mm 304 stainless steel
- Front panels 0.9mm 304 stainless steel • 2.0kW hot plate elements with machine finished 8mm steel plate
- Vitreous enamelled element module spill tray
- Stainless steel hob spill tray
- 2.4kW open radiant elements in heavy-duty welded element frames (optional extra)
- · 12mm thick mild steel griddle plates
- 2.5mm 304 stainless steel griddle splash guards
- · Aluminised steel internal construction
- BENCH MOUNT (SUPPLIED AS -B MODEL)
- Four 63mm dia. heavy-duty 1.2mm 304 stainless steel bench legs with adjustable feet.
- Adjustable height 80mm 105mm

CABINET BASE (SUPPLIED AS -CD MODEL)

- Fully modular for match suite finish
- Double skin 0.9mm 304 stainless steel interior and exterior
- Optional GN 1/1 4 position racking kit (1 or 2 cabinet bays) Up to eight 65mm GN 1/1 capacity
- 63mm dia. heavy-duty 1.2mm 304 stainless steel legs with adjust. feet
- LEG STAND (SUPPLIED AS -LS MODEL)
- Fully modular for matched suite finish
- Framed top for connection to Cooktop
- 63mm dia. heavy-duty 1.2mm 304 stainless steel legs with adjust. feet
- Fully modular framed stand shelf with 0.9mm 304 stainless steel finish
- · Shelf to top stainless steel backstop panel for convenience and rigidity Suitable for rear or through shelf gas connection to Cooktop
- Quick assembly design (no tools required)

REFRIGERATED BASE (SUPPLIED AS -RB MODEL)

· Self contained suite matched modular base

- Ventilated system with R134a refrigerant
- -2° to + 8°C temperature (Tropical Climate rated)
- Two GN 1/1 drawers
- 100mm deep pan drawer capacity
- Heavy-duty European telescopic drawer guides
- Magnetic drawer gaskets (replaceable without tools)
- 50mm fully foamed CFC free insulation
- 304 stainless steel exterior and interior
- Anti-corrosion treated evaporator
- No condensate drain required
- 63mm dia. heavy-duty 1.2mm 304 stainless steel legs with adjust. feet
- Condensing unit removable through front of unit for service
- Easy clean interior
- Refrigerated bases in stainless steel finish only

### CONTROLS

#### COOKTOP

- Large easy use control knob heat resistant reinforced

- · Indicator lights for power and heating for each element control
- REFRIGERATED BASE
- Automatic evaporation of defrost water

#### CLEANING AND SERVICING

- · All models with easy clean stainless steel external finish
- · Stainless steel spill trays under open burner and griddle sections
- Access to all parts from front of unit
- Refrigerated Base condenser removable through front of unit


- Easy view control settings on knob
- · Hot plate elements with energy regulator controls
- Radiant elements with energy regulator controls
  50-320°C thermostat per 300mm griddle section


- Automatic defrost
- -2° to +8°C temperature range



# **Electric Cooktops** 900mm

#### RNLB8600E-B






#### RNLB8600E-CD

RNLB8600E-RB

88 88 88

\_

315



70

8

RNLB8600E-LS



RNLB8600E

SPECIFICATIONS

2.4 kW Open Radiant elements

2.0 kW Hot Plate elements

(per 300mm griddle section)

292mm x 475mm, 1387cm2

592mm x 475mm, 2812cm2

892mm x 475mm, 4237cm2

Electrical requirements

300mm Griddle cooking surface

600mm Griddle cooking surface

900mm Griddle cooking surface

14.4 kW, 400-415Vac, 50/60hz, 3P+N+E,

13.2 kW, 400-415Vac, 50/60hz, 3P+N+E,

12 kW, 400-415Vac, 50/60hz, 3P+N+E,

10.8 kW, 400-415Vac, 50/60hz, 3P+N+E,

130mm from RH side, 31mm from rear 85mm from bench height on bench models

740mm from floor on leg stand and cabinet

3.6 kW Griddle elements

Cooktop

Griddle Plate

**BNI B8600F** 

20A/phase

BNI 88603E

RNLB8606E

**BNI B8609E** 

base models

Refrigerated base

20A/phase max.

20A/phase max.

15A/phase max.

Electrical connection



# RNLB8603E

ELECTRICAL ENTRY



Electrical connection

#### Dimensions

Bench models Width 900mm Depth 805mm Height 315mm Incl. low back 370mm Incl. splashback option 530mm All models (excluding Bench model) Width 900mm Depth 805mm Height 915mm Incl. low back 970mm Incl. splashback option 1130mm Packing data

Bench and Leg Stand models

Width 945mm

#### OPTIONS AT EXTRA COST

(replace individual open radiant elements) Ribbed ariddle plates

an Ali Group Company



moffat.com.au moffat.co.nz

#### Australia moffat.com.au

## Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone +613-9518 3888 Facsimile +613-9518 3833 vsales@moffat.com.au

New South Wales Telephone +612-8833 4111 nswsales@moffat.com.au

South Australia Telephone -613-9518 3888 vsales@moffat.com.au

Queensland Telephone +617-3630 8600

qldsales@moffat.com.au Western Australia Telephone 618-9413 2400

wasales@moffat.com.au New Zealand

moffat.co.nz

22

## Moffat Limited

Rolleston 45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz

Auckland Telephone +64 9-574 3150 sales@moffat.co.nz





Designed and manufactured by

MOFFRT.

ISO9001

All Waldorf Bold products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd AN.WBD.S.01.2020



220-240Vac, 50Hz, 1.8A, 1P+N+E 3 pin 10A plug cordset fitted

0.55m3, 135kg (90kg nett) Width 945mm Depth 870mm Height 665mm Cabinet Base and Refrigerated Base models 1.03m3, 195kg (130kg nett)

Depth 870mm Height 1255mm

Hot Plate elements

Type Ventilated system Refrigerant R134a (160grams) Climate classification T - tropical