

## Modular Cooking Range Line EVO700 4-Hot Plates Electric Boiling Top Range

ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_

AIA # \_\_\_\_\_



372015 (Z7ECEH4R00) 4-hot plate (2,6 kW each)  
electric boiling top

372127 (Z7ECEH4R0N) 4-hot plate (2,6 kW each)  
electric boiling top

### Short Form Specification

Item No. \_\_\_\_\_

To be installed on open base installations, bridging supports or cantilever systems. Four 2.6 kW cast-iron hot plates hermetically sealed to the one-piece top. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

### Main Features

- Unit to be mounted on open base cupboards, bridging supports or cantilever systems.
- The four 2.6kW cast-iron plates are hermetically sealed to the one-piece top.
- The special design of the control knob system guarantees against water infiltration.
- IPx4 water protection.
- Suitable for countertop installation.

### Construction


- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

APPROVAL: \_\_\_\_\_

**Optional Accessories**

- Junction sealing kit PNC 206086
- Support for bridge type installation, 800 mm PNC 206137
- Support for bridge type installation, 1000 mm PNC 206138
- Support for bridge type installation, 1200 mm PNC 206139
- Support for bridge type installation, 1400 mm PNC 206140
- Support for bridge type installation, 1600 mm PNC 206141
- Frontal handrail 800 mm PNC 206167
- Large handrail (portioning shelf) 800 mm PNC 206186
- Frontal handrail 1200 mm PNC 206191
- Frontal handrail 1600 mm PNC 206192
- Right and left side handrails PNC 206240
- Water column with swivel arm (water column extension not included) PNC 206289
- Water column extension PNC 206291
- Chimney upstand, 800 mm PNC 206304
- 2 side covering panels, height 250 mm, depth 700 mm PNC 206320
- Chimney grid net, 400mm PNC 206400

# Modular Cooking Range Line EVO700 4-Hot Plates Electric Boiling Top Range



## Electric

### Supply voltage:

372015 (Z7ECEH4R00) 380-400 V/3 ph/50/60 Hz

372127 (Z7ECEH4RON) 230 V/3 ph/50/60 Hz

### Total Watts:

10.4 kW

### Predisposed for:

372015 (Z7ECEH4R00)

380-400V 3~ 50/60Hz  
9-10,4kW

## Key Information:

Front Plates Power: 2.6 - 2.6 kW

Back Plates Power: 2.6 - 2.6 kW

Front Plates dimensions: Ø 230 Ø 230

Back Plates dimensions: Ø 230 Ø 230

Net weight: 40 kg

Shipping weight: 38 kg

### Shipping height:

372015 (Z7ECEH4R00) 530 mm

372127 (Z7ECEH4RON) 540 mm

### Shipping width:

820 mm

### Shipping depth:

860 mm

### Shipping volume:

372015 (Z7ECEH4R00) 0.37 m<sup>3</sup>

372127 (Z7ECEH4RON) 0.38 m<sup>3</sup>

### Certification group:

372015 (Z7ECEH4R00) EH74T

372127 (Z7ECEH4RON) N7CE1

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.