

# SINGLE PAN ELECTRIC PASTA COOKER 450mm

E47, E47-7

- High performance single pan pasta cooker
  E47 10.5kW 3 phase
  E47-7 7.0kW 1 phase
- Heavy-duty 3 coil Incoloy 825 element
- Easy clean 316 grade stainless steel open pan
- 40L water capacity
- Integrated water fill and starch skimming water faucet
- Six stainless steel pasta baskets supplied
- Hinged basket drain stand
- Safety cut-out thermostat for empty pan/water boil out
- Stainless steel exterior
- Easy clean
- Easy service
- Fully modular



F47

#### Overall Construction

- Pan 1.5mm 316 stainless steel
- Bull nose welded 1.5mm stainless steel
- Splashback 1.2mm stainless steel
- Side panels 1.2mm stainless steel
- Double skin door with 0.9mm stainless exterior
- 25mm (1") skimming overflow and pan drains drain valve
- 63mm dia. heavy-duty 1.2mm stainless steel legs with adjustable feet
- 6 stainless steel baskets with moulded handles
- Stainless steel wire basket support grid in pan

#### Controls

- Large easy to use knob heat resistant reinforced
- 3 power settings (boil-simmer-standby)
- Mechanical thermostat
- Thermostat range 30°C 110°C
- Fail safe over-temperature safety cut-out
- Element tilt switch for heating cut-out
- Indicator lights for power & heating
- Fine adjustment water faucet for pan filling and water refreshing/ starch skimming

### Cleaning and Servicing

- Open stainless steel pan for easy clean
- Hinged basket drain stand
- Removable basket support grid
- 25mm (1") drain valve for effective draining
- Easy clean stainless steel exterior
- Access to all parts from front of unit



## SINGLE PAN ELECTRIC PASTA COOKER 450mm

E47, E47-7

#### **Specifications**

Pan Size

Water capacity 40L Width 365mm

Length 405mm

Basket immersion depth 165mm

6 stainless steel perforated baskets with moulded plastic handles 125mm x 165mm x 180mm deep Stainless steel wire basket support grid

1 x 10.5kW Incoloy 825 heating element (E47)

1 x 7.0kW Incoloy 825 heating element (E47-7)

#### **Electrical Requirements**

10.5kW, 400-415V, 50/60Hz, 3P+N+E

L1 14.6A

L2 14.6A

L3 14.6A

F47-7

7.0kW, 220-240V, 50/60Hz, 1P+N+E

L1 29.2A

#### **Electrical Connection**

56mm from RH side, 541mm from rear and 489mm from floor

Water Connection

Cold water connection 50mm from left hand side,

556mm from rear and 150mm from floor

 $R^{1}/_{2}$  (BSP) male

550kPa 80psi maximum water pressure

#### Drain Connection

Drain must be connected to system suitable for boiling water discharge

1" BSP Male connection 118mm from left hand side, 470mm from rear, and 170mm from floor

#### **Dimensions**

Width 450mm

Depth 812mm

Height 915mm

Incl. splashback 1085mm

### Nett weight

78kg

### Packing data


0.54m3, 120kg

Width 870mm

Depth 495mm

Height 1255mm

Rectangular baskets 320mm x 165mm x 180mm deep Square baskets 165mm square x 180mm deep Side splash guards Joining caps







## **MOFFAT**

#### moffat.com.au moffat.co.nz

Australia moffat.com.au

#### Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone +613-9518 3888 Facsimile +613-9518 3833 vsales@moffat.com.au

New South Wales Telephone +612-8833 4111 nswsales@moffat.com.au

South Australia Telephone +613-9518 3888 vsales@moffat.com.au

Queensland Telephone +617-3630 8600 qldsales@moffat.com.au

Western Australia Telephone +618-9413 2400 wasales@moffat.com.au

#### New Zealand moffat.co.nz

#### Moffat Limited

Rolleston 45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz

Auckland Telephone +64 9-574 3150 sales@moffat.co.nz





IS09001 Quality Management

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd AN.BSE.02.19/1620

The Spirit of Excellence