

# VEE RAY TWIN PAN GAS FRYER 450mm

GT46

- Twin pan fryer flexibility full single pan performance
- Patented infra-red burner system
- High performance fast recovery
- Easy clean stainless steel open pan with 10 year limited warranty
- 13L oil capacity per pan
- Large capacity cool zones
- 32mm (1 <sup>1</sup>/<sub>4</sub>") drain valves
- Rear rollers
- Stainless steel exterior
- Easy service
- Fully modular



GT46

# Overall Construction

- Stainless steel pan with 10 year limited warranty
- Bull nose welded 1.5mm 304 stainless steel
- Splashback 1.2mm 304 stainless steel
- Side panels 1.2mm 304 stainless steel
- Double skin door with 0.9mm 304 stainless exterior
- Vitreous enamelled front panel
- $\bullet$  32mm (1  $^{1}/_{4}$ ") drain valve per pan
- 63mmdia.heavy-duty1.2mm304stainlesssteeladjustablelegsatfront and two rollers at rear
- 2 baskets and stainless steel lid supplied standard

# Controls

- Direct action thermostats react to + or 1.0°C
- Thermostat range 145 195°C
- Over-temperature safety cut-outs
- Millivolt gas valve system (no electrical supply)
- Flame failure protection on each pilot
- Piezo ignition to standing pilot burners

# Cleaning and Servicing

- Open stainless steel pans for easy clean
- Easy clean basket support bar
- ullet 32mm (1  $^1/4$ ") drain valves for effective draining
- Easy clean stainless steel exterior
- Access to all parts from front of unit





# VEE RAY TWIN PAN GAS FRYER 450mm

GT46

### **Specifications**

#### Production rate

31kg/hr

#### Pan Size

Oil capacity 13L (24lbs shortening) per pan Width 175mm Length 380mm Oil frying depth 95mm

#### **Baskets**

2 chrome plated wire baskets 140mm W x 335mm D x 145mm H Stainless steel perforated basket support plates

#### Burners

 $1 \times 45 MJ/hr$  infra-red burner per pan

#### **Gas Power**

90MJ/hr, 25kW total

#### Gas connection

R <sup>3</sup>/<sub>4</sub> (BSP) male Optional rear connection

(refer specification drawing)

#### Dimensions

Width 450mm Depth 812mm

Height 915mm Incl. splashback 1085mm

# Nett weight

88kg

# Packing data

0.54m3, 129kg

Width 870mm

Depth 495mm

Height 1255mm

# Gas types

Available in Natural gas and LP gas, please specify when ordering  $% \left( 1\right) =\left( 1\right) \left( 1\right)$ 

Units supplied complete with gas type

conversion kits

Other gas types on request

#### Options


Adjustable feet at rear Filtamax Filtration System

Fish plates Extra baskets

Side splash guards

Joining caps

Castors





# MOFFAT

# moffat.com.au moffat.co.nz

Australia moffat.com.au

#### Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone +613-9518 3888 Facsimile +613-9518 3833 vsales@moffat.com.au

New South Wales Telephone +612-8833 4111 nswsales@moffat.com.au

South Australia Telephone +613-9518 3888 vsales@moffat.com.au

Queensland Telephone +617-3630 8600 qldsales@moffat.com.au

Western Australia Telephone +618-9413 2400 wasales@moffat.com.au

#### New Zealand moffat.co.nz

### Moffat Limited

Rolleston 45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz

Auckland Telephone +64 9-574 3150 sales@moffat.co.nz





ISO9001 Quality Management Standard



Cert. No. 6882

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd AN.BSE.01.19/1620