



# Blue Seal Electric Combi Steamer COMPACT SAPIENS RELOADED EC1011RSDW 10 x 1/1 GN



- · Compact 510mm wide
- Manual controls
- Electric direct steam version
- LED HVS (High Visibility System) alphanumeric display for temperature, Autoclima, time and core temperature
- 2.4" LCD-TFT colour display with rapid selection scroller knob for program and setting selection
- Two speed fan
- Over 95 preset recipe programs
- 99 free programs with up to 9 cycles in automatic sequence
- Electronic thermostat 30° 300°C
- · Manual pre-heating
- Auto-reversing fan rotation
- · Autoclima with automatic vent
- Fast-Dry, quick dehumidification of the cooking chamber
- Multipoint core temperature probe
- Automatic LCS (Liquid Clean System) with built-in tank and automatic dispensing
- ECOVAPOR automatic control of the steam saturation in the cooking chamber
- ECOSPEED oven optimizes and controls the delivery of energy to maintain correct cooking temperature
- · Externally connected hand shower
- USB connection

#### **GENERAL FEATURES**

- Direct Steam injection system
- Perfectly smooth, water tight chamber
- Double tempered glass door with air chamber and interior heat-reflecting glass reduces head radiation towards operator
- Hinged inner glass for easy cleaning
- Adjustable door hinge for optimal seal
- Fan motor thermic protection
- Low water alarm
- Component cooling system with overhear display control
- Self-diagnosis and fault display
- Oven light
- IPX4 spray-proof and hose proof

#### OPTIONAL FEATURES

- Right hinged door
- Configuration for connection to extraction hood







**ECOVAPOR** 







ECO WASH

TOCLIMA FAST-

AUTOMA





## Blue Seal Electric Combi Steamer COMPACT SAPIENS RELOADED EC1011RSDW 10 x 1/1 GN

#### Dimensions

Width 510mm 800mm Depth Height 1120mm Weight 79kg

#### Packed dimensions

Width 570mm Depth 930mm Height 1260mm Weight 88kg

#### **Shelves**

1/1 GN Shelf Spacings 60mm

#### Installation requirements

(for precise installation instructions, please refer to the unit's installation manual).

#### Power connection requirements

Multi pole circuit breaker and all pole disconnection isolator switch installed near the appliance.

#### Supply line voltage

400-415V - 50Hz, 3P+N+E

Special voltage options available on request.

#### Power connection

15.5 Total (kW) Convection power (kW) 15 Rated Current (A) (400V) 23

#### Installation clearances

- rear 50mm - right 500mm\* - left 50mm
- \*Clearance required on fixed installations for service accessibility.

If heat sources are located near the RH side of the Sapiens combi, ensure that a minimum distance of 500mm is maintained.

Install in accordance with local body regulations only on horizontal surfaces and not against combustible walls.

#### Water connection requirements

- Cold water
- Flow pressure (200-500kPa)
- Soft water connection\*
- Shut-off valve with return flow inhibitor and dirt filter
- Water supply x2 R3/4
- R40 waste water connection

(\*Water softener may be required. Please refer to installation manual for water treatment values.)

### MOFFE

Australia www.moffat.com.au

New Zealand www.moffat.co.nz

#### Australia Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone 03-9518 3888 Facsimile 03-9518 3833 vsales@moffat.com.au

**New South Wales** Telephone 02-8833 4111 nswsales@moffat.com.au

South Australia Telephone 03-9518 3888 vsales@moffat.com.au

Queensland Telephone 07-3630 8600 qldsales@moffat.com.au

Western Australia Telephone 08-9413 2400 wasales@moffat.com.au

#### New Zealand Moffat Limited

#### Rolleston

45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone 03-983 6600 Facsimile 03-983 6660 sales@moffat.co.nz

#### Auckland


Telephone 09-574 3150 sales@moffat.co.nz

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.


© Copyright Moffat Ltd Moffat 1569 / 18.05



















o3/4 ø3/4

**F** 

Ϋ́Υ







