



Blue Seal Electric Combi Steamer COMPACT SAPIENS RELOADED EC623RSDW 6 x 2/3 GN



- · Compact 510mm wide
- Manual controls
- Electric direct steam version
- LED HVS (High Visibility System) alphanumeric display for temperature, Autoclima, time and core temperature
- 2.4" LCD-TFT colour display with rapid selection scroller knob for program and setting selection
- Two speed fan
- Over 95 preset recipe programs
- 99 free programs with up to 9 cycles in automatic sequence
- Electronic thermostat 30° 300°C
- Manual pre-heating
- · Auto-reversing fan rotation
- · Autoclima with automatic vent
- Fast-Dry, quick dehumidification of the cooking chamber
- Multipoint core temperature probe
- Automatic LCS (Liquid Clean System) with built-in tank and automatic dispensing
- ECOVAPOR automatic control of the steam saturation in the cooking chamber
- ECOSPEED oven optimizes and controls the delivery of energy to maintain correct cooking temperature
- · Externally connected hand shower
- USB connection

GENERAL FEATURES

- Direct Steam injection system
- Perfectly smooth, water tight chamber
- Double tempered glass door with air chamber and interior heat-reflecting glass reduces head radiation towards operator
- Hinged inner glass for easy cleaning
- Adjustable door hinge for optimal seal
- Fan motor thermic protection
- Low water alarm
- Component cooling system with overhear display control
- Self-diagnosis and fault display
- Oven light
- IPX4 spray-proof and hose proof

OPTIONAL FEATURES

- Right hinged door
- Configuration for connection to extraction hood







ECOVAPOR







ECO WASH

AUTO





Blue Seal Electric Combi Steamer COMPACT SAPIENS RELOADED EC623RSDW 6 x 2/3 GN

Dimensions

Width 510mm Depth 625mm Height 880mm Weight 59kg

Packed dimensions

Width 570mm Depth 760mm Height 1020mm Weight 68kg

Shelves

2/3 GN 6 Shelf Spacings 60mm

Installation requirements

(for precise installation instructions, please refer to the unit's installation manual).

Power connection requirements

Multi pole circuit breaker and all pole disconnection isolator switch installed near the appliance.

Supply line voltage

400-415V - 50Hz, 3P+N+E

Special voltage options available on request.

Power connection

Total (kW) 5.25 Convection power (kW) 5 Rated Current (A) (400V) 8

Installation clearances

- rear 50mm - right 500mm* - left 50mm
- *Clearance required on fixed installations for service accessibility.

If heat sources are located near the RH side of the Sapiens combi, ensure that a minimum distance of 500mm is maintained.

Install in accordance with local body regulations only on horizontal surfaces and not against combustible walls.

Water connection requirements

- Cold water
- Flow pressure (200-500kPa)
- Soft water connection*
- Shut-off valve with return flow inhibitor and dirt filter
- Water supply x2 R3/4
- R40 waste water connection

(*Water softener may be required. Please refer to installation manual for water treatment values.)

MOFFRT

Australia www.moffat.com.au

New Zealand www.moffat.co.nz

Australia Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone 03-9518 3888 Facsimile 03-9518 3833 vsales@moffat.com.au

New South Wales Telephone 02-8833 4111 nswsales@moffat.com.au

South Australia Telephone 03-9518 3888 vsales@moffat.com.au

Queensland Telephone 07-3630 8600 qldsales@moffat.com.au

Western Australia Telephone 08-9413 2400 wasales@moffat.com.au

New Zealand Moffat Limited

Rolleston

45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone 03-983 6660 Facsimile 03-983 6660 sales@moffat.co.nz

Auckland


Telephone 09-574 3150 sales@moffat.co.nz


In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.


© Copyright Moffat Ltd Moffat 1569 / 18.05






































an Ali Group Company

