




MLB BREAST MILK REFRIGERATOR

NULINE
REFRIGERATION

FEATURES

- Fan Forced System
- Voltage Free Connection
- Door Lock
- Door Ajar Alarms
- Interior LED Lighting
- Automatic Condensate Water Disposal
- Fan Door Switch
- Data Logger included
- Battery Backup for Controller
- Digital Display with Built-in Alarms
- Hi/Lo Readout
- Self-closing Doors



	2°C to 4°C
	29 L 59 L 125 L
	445w x 458d x 535h 450w x 460d x 875h 595w x 610d x 840h

MLB BREAST MILK REFRIGERATOR



Model	MLB29G	MLB59G	MLB125G
Gross Capacity	29 L	59 L	125 L
External Dimensions in mm (w/d/h including castors)	445 x 458 x 535	450 x 460 x 875	595 x 610 x 840
Internal Dimensions in mm (w/d/h)	361 x 205 x 400	390 x 300 x 720	505 x 442 x 625
Packed Dimensions in mm (w/d/h including pallet)	500 x 575 x 590	525 x 560 x 900	660 x 705 x 910
Gross Weight - kg (packed weight)	30	41	59
Net Weight - kg	27	38	55
Voltage	240V		
Temperature Range	2°C to 4°C		
Ambient Temperature Range	10°C to 32°C		
Refrigerant	R600		
Cooling System / Defrost	Fan Forced / Automatic		
Exterior Cabinet Finish	Enamelled Steel		
Inner Liner Material	ABS		
Door	Glass		
Door Hinge	RH		
Door Handle	Pull Handle		
Type of Controller	Digital		
Temperature Display	External		
Data Logger	Included		
Door Ajar Alarms	Yes		
High and Low Readout	Visual / Audible		
BMS Connectivity			
(BMS Connectivity for Remote Alarms only)	Yes		
(BMS Connectivity for 4-20mA Transmitter)	Optional		
Port Entry	Yes		
Battery Back-up for Controller	Yes		
Power Requirement	10amp GPO		
Watts	125		
Castors	Adjustable Levelling Legs		
Adjustable Shelves	2	3	4
Usable Shelf Area in mm(w/d)	2 x 376 x 190	2 x 368 x 287 1 x 378 x 190	2 x 488 x 411 2 x 488 x 276
Light	LED		

Nuline Refrigeration reserves the right to alter the specifications without prior notice.