



MLS 125 STATIC REFRIGERATOR

NULINE
REFRIGERATION

FEATURES

- Static Refrigeration System
- Voltage Free Connection
- Door Lock
- Door Ajar Alarms
- Battery Backup for Controller
- Digital Display with Built-in Alarms
- Hi/Lo Readout



	2°C to 8°C
	125 L
	595w x 595d x 840h



MLS 125 STATIC REFRIGERATOR



Model	MLS125GP	MLS125P
Gross Capacity	125 L	125 L
External Dimensions in mm (w/d/h including castors)	595 x 595 x 840	
Internal Dimensions in mm (w/d/h)	510 x 410 x 680	
Packed Dimensions in mm (w/d/h including pallet)	695 x 595 x 970	
Gross Weight - kg (packed weight)	68	
Net Weight - kg	55	
Voltage	240V	
Temperature Range	2°C to 8°C	
Ambient Temperature Range	10°C to 32°C	
Refrigerant	R600	
Cooling System / Defrost	Static / Manual	
Exterior Cabinet Finish	White Enamel	
Inner Liner Material	White Enamel	
Door	Glass	Solid
Door Hinge	RH	
Door Handle	Pull Handle	
Type of Controller	Digital	
Temperature Display	External	
Data Logger	Yes	
Door Ajar Alarms	Yes	
High and Low Readout	Visual / Audible	
BMS Connectivity (BMS Connectivity for Remote Alarms only)	Yes	
(BMS Connectivity for 4-20mA Transmitter)	Optional	
Port Entry	Yes	
Battery Back-up for Controller	Yes	
Power Requirement	10amp GPO	
Castors	No	
Adjustable Shelves	4	
Usable Shelf Area in mm(w/d)	2 x 488 x 411 & 2 x 488 x 276	



Nuline Refrigeration reserves the right to alter the specifications without prior notice.