




NLMS SPARK SAFE LABORATORY REFRIGERATOR

NULINE
REFRIGERATION

FEATURES

- Top Mounted System
- E-glass and heated cabinet facia to prevent condensation up to 80% R.H.
- Glass or Solid Door
- Auto Water Disposal
- Hot Gas Defrost
- Castors
- Door Lock
- Digital Display with Built-in Alarms
- Hi/Lo Readout
- TGA Certified



| | |
|---|--|
|  | 2°C to 8°C |
|  | 400 L 700 L 1000 L 1614 L |
|  | 600w x 620d x 1915h 870w x 700d x 2100h 1200w x 700d x 2100h 1880w x 700d x 2100h |



NLMS SPARK SAFE LABORATORY REFRIGERATOR



| Model | NLMS400/1 | NLMS700/1 | NLMS1000/2 | NLMS1614/3 |
|---|-----------------------|------------------|-------------------|-------------------|
| Gross Capacity | 400 L | 700 L | 1000 L | 1614 L |
| External Dimensions in mm (w/d/h including castors) | 600 x 620 x 1915 | 870 x 700 x 2100 | 1200 x 700 x 2100 | 1880 x 700 x 2100 |
| Internal Dimensions in mm (w/d/h) | 500 x 470 x 1435 | 770 x 550 x 1555 | 1100 x 550 x 1555 | 1780 x 550 x 1520 |
| Packed Dimensions in mm (w/d/h including pallet) | 700 x 720 x 2065 | 970 x 800 x 2250 | 1300 x 800 x 2250 | 1980 x 800 x 2250 |
| Gross Weight - kg (packed weight) | 102 | 112 | 137 | 187 |
| Net Weight - kg | 95 | 95 | 125 | 175 |
| Voltage | 240V | | | |
| Temperature Range | 2°C to 8°C | | | |
| Ambient Temperature Range | 10°C to 32°C | | | |
| Refrigerant | R134a | | | |
| Cooling System / Defrost | Static | | | |
| Exterior Cabinet Finish | White Colourbond | | | |
| Inner Liner Material | White Colourbond | | | |
| Door | Solid / Glass E-Glass | | | |
| Door Hinge | RH | | LH / RH | LH / RH / RH |
| Door Handle | Lockable | | | |
| Type of Controller | Digital | | | |
| Temperature Display | External | | | |
| Data Logger | Optional | | | |
| Door Ajar Alarms | Optional | | | |
| High and Low Readout | Visual / Audible | | | |
| BMS Connectivity | | | | |
| (BMS Connectivity for Remote Alarms only) | Optional | | | |
| (BMS Connectivity for 4-20mA Transmitter) | Optional | | | |
| Port Entry | Optional | | | |
| Battery Back-up for Controller | Optional | | | |
| Power Requirement | 10amp GPO | | | |
| Castors | Yes | | | |
| Adjustable Shelves | | 5 | | 15 |
| Usable Shelf Area in mm(w/d) | 480 x 450 | 750 x 530 | 1080 x 530 | 565 x 530 |
| Light | LED | | | |

Nuline Refrigeration reserves the right to alter the specifications without prior notice.

NLMS SPARK SAFE LABORATORY REFRIGERATOR

NULINE
REFRIGERATION

Since 1985, Nuline Refrigeration has been manufacturing refrigerators and freezer cabinets for the Australian market. Our specialised range of biomedical cabinets are used extensively across the hospitals, medical centres, pharmacies and laboratories.

Focusing on customer needs, we manufacture, import and customise the biomedical cabinets from a range of selected global suppliers. Our factory is based in Melbourne, Australia and we are proudly 100% Australian owned business.

Each of our manufactured cabinets are custom built based on customer orders by our craftsmen right here in Melbourne.

We have extensive capability to design, engineer and build a range of refrigerated cabinets for you. Our standard product range includes, fridges, freezers (up to -40°C), blanket warmer, mortuary refrigerators and refrigerated incubators.

